



Material Safety Data Sheet

Revision Date: 27-Dec-2011

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name COROPOXY SURFACE TOLERANT MASTIC BASE
Product Code 113 Series
Product Class
Color All

Manufacturer
 Complementary Coatings Corp.
 dba Insl-X
 101 Paragon Drive
 Montvale, NJ 07645
 Phone: (800)-225-5554
 www.insl-x.com

Emergency Telephone Number(s)
 CHEMTREC (US): 800-424-9300
 CHEMTREC (outside US): (703)-527-3887

2. COMPOSITION INFORMATION ON COMPONENTS

Hazardous Components

Chemical Name	CAS-No	Weight % (max)
Polyamine		25
Kaolin, calcined	66402-68-4	20
Titanium dioxide	13463-67-7	20
Silica, crystalline	14808-60-7	15
Xylene	1330-20-7	10
Talc	14807-96-6	5
Propylene glycol monomethyl ether	107-98-2	5
Ethyl benzene	100-41-4	5
Triethylenetetramine	112-24-3	5
Solvent naphtha, petroleum, light aromatic	64742-95-6	5
Propylene glycol monomethyl ether acetate	108-65-6	5
2-Butoxyethanol	111-76-2	0.5

3. HAZARDS IDENTIFICATION

3. HAZARDS IDENTIFICATION

Emergency Overview

DANGER

Vapor harmful. Harmful by inhalation. Harmful if swallowed. Irritating to eyes. Irritating to skin. May cause allergic skin reaction.. Irritating to respiratory system. May cause allergic respiratory reaction. Flammable.

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components.
CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, a small amount of clean sand may be added. Stir often during application.

Appearance liquid

Odor Not available

OSHA Regulatory Status This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Effects

Eyes

Causes eye irritation. Avoid contact with eyes. Vapor may cause irritation with symptoms of burning and tearing.

Skin

Irritating to skin. Avoid contact with skin. May cause skin sensitization. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be absorbed through the skin in harmful amounts.

Inhalation

Irritating to respiratory system. Avoid breathing vapors or mists. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects. May cause respiratory sensitization.

Ingestion

Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death..

Chronic Effects

Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Can be absorbed through skin.

Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Skin disorders. Asthma and other respiratory disorders. Kidney disorders. Auditory system disorders. Pre-existing heart disorders.

HMIS

Health: 2*

Flammability: 3

Reactivity: 0

PPE: -

HMIS Legend

0 - Minimal Hazard
1 - Slight Hazard
2 - Moderate Hazard
3 - Serious Hazard
4 - Severe Hazard
* - Chronic Hazard
X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

4. FIRST AID MEASURES

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothing and shoes., Consult a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
Notes To Physician	Treat symptomatically
Protection Of First-Aiders	Use personal protective equipment

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Flammable. Closed containers may rupture if exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	Yes
Flash Point Data	
Flash Point (°F)	80
Flash Point (°C)	27
Flash Point Method	PMCC
Flammability Limits In Air	
Lower Explosion Limit	Not available
Upper Explosion Limit	Not available

NFPA **Health:** 2 **Flammability:** 3 **Instability:** 0 **Special:** Not Applicable

NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.. Use personal protective equipment. Remove all sources of ignition.. Take precautionary measures against static discharges.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Methods For Clean-Up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.
Other Information	None known

7. HANDLING AND STORAGE

Handling	Keep in a well-ventilated place. Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.. In case of insufficient ventilation, wear suitable respiratory equipment. Remove and wash contaminated clothing before re-use.
-----------------	--

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Hazardous Components

Chemical Name	ACGIH	OSHA
Polyamine	N/E	N/E
Kaolin, calcined	0.2 mg/m ³ - TWA 5 mg/m ³ - TWA 10 mg/m ³ - STEL	5 mg/m ³ - TWA
Titanium dioxide	10 mg/m ³ - TWA	15 mg/m ³ - TWA total
Silica, crystalline	0.025 mg/m ³ - TWA	respirable - (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable - (250)/(%SiO ₂ + 5) mppcf TWA total dust - (30)/(%SiO ₂ + 2) mg/m ³ TWA
Xylene	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 435 mg/m ³ - TWA
Talc	2 mg/m ³ - TWA	20 mppcf - TWA
Propylene glycol monomethyl ether	100 ppm - TWA 150 ppm - STEL	N/E
Ethyl benzene	100 ppm - TWA 125 ppm - STEL	100 ppm - TWA 435 mg/m ³ - TWA
Triethylenetetramine	N/E	N/E
Solvent naphtha, petroleum, light aromatic	N/E	N/E
Propylene glycol monomethyl ether acetate	N/E	N/E
2-Butoxyethanol	20 ppm - TWA	240 mg/m ³ - TWA 50 ppm - TWA prevent or reduce skin absorption

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields. If splashes are likely to occur, wear:.. Tightly fitting safety goggles. Face-shield.

Skin Protection

Long sleeved clothing. Protective gloves.. Boots.

Respiratory Protection

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	Not available
Density (lbs/gal)	10.9 - 12.8
Specific Gravity	1.3 - 1.6
pH	Not available
Viscosity (centistokes)	Not available
Evaporation Rate	Not available
Vapor Pressure	Not available
Vapor Density	Not available
Wt. % Solids	75 - 95
Vol. % Solids	65 - 85
Wt. % Volatiles	5 - 25
Vol. % Volatiles	15 - 35
VOC Regulatory Limit (g/L)	<250
Boiling Point (°F)	246
Boiling Point (°C)	119
Freezing Point (°F)	Not available
Freezing Point (°C)	Not available
Flash Point (°F)	80
Flash Point (°C)	27
Flash Point Method	PMCC
Upper Explosion Limit	Not available
Lower Explosion Limit	Not available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions To Avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Component

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)
LD50 Dermal: > 10000 mg/m³ (Rabbit)
LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

Silica, crystalline

LD50 Oral: 500 mg/kg (Rat) vendor data

Xylene

LD50 Oral: 4300 mg/kg (Rat)
LD50 Dermal: > 1700 mg/kg (Rabbit)
LC50 Inhalation (Vapor): 5000 ppm (Rat, 4 hr.)
Sensitization: No sensitizing effects known.

Propylene glycol monomethyl ether

LD50 Oral: 6,600 mg/kg (Rat)
LD50 Dermal: 13,000 mg/kg (Rabbit)
LC50 Inhalation (Vapor): 10,000 ppm (Rat)

Ethyl benzene

LD50 Oral: 3500 mg/kg (Rat)
LD50 Dermal: > 5000 mg/kg (Rabbit)
LC50 Inhalation (Vapor): 55000 mg/m³ (Rat, 2 hr.)
Sensitization: No sensitizing effects known.

Triethylenetetramine

LD50 Oral: 2500 mg/kg (Rat)
LD50 Dermal: 805 mg/kg (Rabbit)

Solvent naphtha, petroleum, light aromatic

LD50 Oral: 8400 mg/kg (Rat)

Propylene glycol monomethyl ether acetate

LD50 Oral: 8532 mg/kg (Rat)
LD50 Dermal: > 5000 mg/kg (Rabbit)
LC50 Inhalation (Vapor): > 4345 ppm

2-Butoxyethanol

LD50 Oral: 470 mg/kg (Rat)
LD50 Dermal: 220 mg/kg (Rabbit)
LC50 Inhalation (Vapor): 2.2 mg/L (Rat, 4 hr.)
Sensitization: No sensitizing effects known.

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
Kaolin, calcined		2B - Possible Human Carcinogen		
Titanium dioxide		2B - Possible Human Carcinogen		Listed
Silica, crystalline	A2 - Suspected Human Carcinogen	1 - Human Carcinogen	Known Human Carcinogen	Listed
Ethyl benzene	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	2B - Possible Human Carcinogen		Listed
2-Butoxyethanol	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans			

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
 IARC - International Agency for Research on Cancer
 NTP - National Toxicity Program
 OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

Product

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

12. ECOLOGICAL INFORMATION

Component

Acute Toxicity to Fish

No information available

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

No information available

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name	Paint
Hazard Class	3
UN-No	UN1263
Packing Group	III

ICAO / IATA

Contact the preparer for further information.

14. TRANSPORT INFORMATION

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

United States TSCA

Yes - All components are listed or exempt.

Canada DSL

Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>
Kaolin, calcined	66402-68-4	20
Xylene	1330-20-7	10
Ethyl benzene	100-41-4	5
2-Butoxyethanol	111-76-2	0.5

This product may contain trace amounts of (other) SARA reportable chemicals. Contact the preparer for further information.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>
Xylene	1330-20-7	10
Ethyl benzene	100-41-4	5
2-Butoxyethanol	111-76-2	0.5

This product may contain trace amounts of (other) HAPs chemicals. Contact the preparer for further information.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
Kaolin, calcined		X	X		X
Titanium dioxide	X	X	X		X
Silica, crystalline	X	X	X		X
Xylene	X	X	X		X
Talc	X	X	X		X
Propylene glycol monomethyl ether	X	X	X		X
Ethyl benzene	X	X	X		X
Triethylenetetramine	X	X	X		
2-Butoxyethanol	X	X	X		X

Legend

X - Listed

16. OTHER INFORMATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Complementary Coatings Corp.
dba Insl-X
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-800-225-5554

Revision Date: 27-Dec-2011
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of MSDS