

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

820.211.1

ACGIH TLV/STEL: STEL 25 ppm
OSHA PEL/TWA: TWA 100 ppm
OSHA STEL: 125 ppm
LD50: Oral, Rat - 3500 mg/kg
CA PROPOSITION 65: Yes

5 PETROLEUM SPIRITS

CAS# 8032-32-4
VM & P NAPHTHA
PCT BY WT: 1 - 5 VAPOR PRESSURE: 5.000 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 300 ppm
OSHA PEL/TWA: TWA 300 ppm
OSHA STEL: 400 ppm
LC50: Inhalation, Rat - 3400 ppm/4H
LD50: Intravenous, Mouse - 40 mg/kg

6

CAS# 13463-67-7
TITANIUM DIOXIDE
PCT BY WT: 3 - 7
EXPOSURE LIMIT:
ACGIH TLV/TWA: 10 mg/cu m(Total Dust) - TWA
OSHA PEL/TWA: 10 mg/cu m(Total Dust) - TWA
LD50: Oral (Rat)- >10000 mg/kg

7 GROUND LIMESTONE

CAS# 1317-65-3
CALCIUM CARBONATE
PCT BY WT: 10 - 30
EXPOSURE LIMIT:
ACGIH TLV/TWA: 2 mg/m3 TLV

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains pigments, which may become a dust nuisance when
removed by abrasive blasting, sanding, or grinding.

This product contains one or more reported or suspected reproductive
toxins.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

820.211.1

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: May cause eye damage and pain.

SKIN: May irritate skin.

INHALATION: Anesthetic. Nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May irritate nose, throat and respiratory tissue.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

CHRONIC OVEREXPOSURE

Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause respiratory and/or skin sensitization.

XYLENE: Studies have shown a possible association with exposure to xylene and respiratory tract irritation, liver and kidney damage, nausea and vomiting in humans.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

Based on an IARC conclusion that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black" and inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "carbon black is possibly carcinogenic to humans" (Group 2B).

Carbon black has not been listed as a carcinogen by the NTP or OSHA. NIOSH criteria document recommends that only carbon blacks with PAH (polynuclear aromatic hydrocarbons) levels > 0.1% be considered suspect carcinogens.

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen, Group 2B.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

820.211.1

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills in a confined area, use self-contained non-sparking tools. Keep out of drains, sewers and waterways.

CLEAN-UP

Contain and remove with inert absorbent and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Do not store above 120 Degrees F. Close container after each use.

SPECIAL COMMENTS

Do not take internally. Wash with soap and water before eating, drinking, smoking or using toilet.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV of the most hazardous ingredient in Section 2, below acceptable limit, and LEL in Section 5 below stated limit, during application of this product, and to remove decomposition products during welding or flame cutting on surfaces coated with this product.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH for protection against chemicals in Sections (2 &/or 15).

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

820.211.1

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
DOT PACKAGING GROUP : PG III
DOT LABEL : FLAMMABLE LIQUID
DOT SHIPPING NAME : PAINT
DOT PLACARD : FLAMMABLE LIQUID
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

XYLENE (MIXED ISOMERS)

CAS# 1330-20-7 PCT BY WT: 7 - 13

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: 2.9520

ZINC PHOSPHATE

CAS# 7779-90-0 PCT BY WT: 1 - 5

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 09/02/2009
Last Revision Date : 03/27/2009
MSDS Prepared for :

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

820.211.1

MSDS Last Prepared : NONE
HMIS Rating: Health- 2* Flammability- 3
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200 (g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.