



CORONADO
P A I N T

SECTION NO. 7
ADS – 809
114 Line
Rev. 10/11

Super Kote 5000™
Latex Oil Barn & Fence Paint
114 Line

Type Latex Oil	Sheen Flat	Theoretical Spread Rate 300 – 450 Sq. Ft. Per Gallon*	Recommended Application Brush, Roller or Spray	Thinner Clean Water	Clean Up Warm Soapy Water
Dry Time:		Tack Free: 30 Minutes	Recoat: 4 Hours	Full Cure: 7 – 10 Days	

PRODUCT NAME: 114 Line Super Kote 5000™ Latex Oil Barn & Fence Paint	Super Kote 5000™ Latex Oil Barn & Fence Paint is designed to reduce the high cost of maintaining out buildings and fences while retaining good protective qualities. It may be used on exterior wood, masonry and primed metal surfaces such as barns, cribs, fences or stalls.	
WHERE TO USE:	Barns Fences Cribs (corn & feed) Stalls	Latex Oil Barn & Fence Paint is specifically formulated for out buildings and fences. For exterior application only on barn siding, corncribs, furrowing houses, pump houses, storage buildings, stalls, fences, etc. Do not apply to horizontal surfaces. Not recommended for siding on residential structures.

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	The products supported by this data sheet contain a maximum of 100 grams per liter VOC / VOS (0.83 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Flat Coating.	This product is not currently certified under MPI. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.

SURFACE PREPARATION:	<p>The surface to be coated must be clean and free of dirt, excessive chalk, mildew, and flaking paint. Pressure washing is a fast and efficient way to remove dirt, chalk, flaking paint, loose wood fibers, cobwebs or other similar surface contamination that could interfere with proper adhesion. If a pressure washer is not available, a conscientious scraping and wire brushing will suffice. Prior to painting, all mildew must be removed by washing the effected surface with a solution of one part household bleach and three parts water. Rinse well with clean water and allow it to dry thoroughly before painting. Wear eye protection devices, rubber gloves and protective clothing when working with bleach. Any glossy surfaces should be dulled by lightly sanding.</p> <p>Priming: (New or Bare Surfaces): Wood – Self Priming Masonry – Self Priming Ferrous Metal – Use CORONADO® Primer 35-111, 35-147, 35-153, 36-11 Non – Ferrous Metal – Use Perma Bond 100-10 Galvanized – Use Perma Bond 100-10</p>
APPLICATION:	New Work – Stir product thoroughly prior to use and periodically during application. Super Kote 5000™ Latex Oil Barn Paint may be applied by brush, roller or spray at up to 450 square feet per gallon. Apply directly to bare wood, as this paint is self-priming. Latex Oil Barn Paint is not recommended for siding on houses, which are usually well sealed from previous coatings, as shiners could occur.

	<p>Repaint Work: After proper surface preparation, apply one or two coats of Super Kote 5000™ Latex Oil Barn & Fence Paint. Bare areas should be spot primed with indicated primer.</p> <p>Do not apply when surface or air temperatures are below 50° F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening. Not recommended for horizontal surfaces.</p>
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
COLORS / TINTING:	Latex Oil Barn & Fence Paint is available in White and Barn Red. Do not tint.
RESIN TYPE:	Vinyl Acetate/Acrylic and Linseed Oil Alkyd
SOLIDS:	Weight: 48.4 ± 1.0% Volume: 33.1 ± 1.0%
WEIGHT PER GALLON:	10.8 lbs.
VISCOSITY:	85 – 90 KU (Krebs Units)
FLASH POINT:	200° F. or greater (TT-P-141, Method 4293)
SPECULAR GLOSS:	5 – 10 units @ 85 Degrees
SAG RATING:	Pass 8 mils (Leneta)
REC. FILM THICKNESS:	Wet: 3.6 to 5.3 mils Dry: 1.2 to 1.8 mils
QUALIFICATIONS:	Latex Oil Barn & Fence Paint is safe for use on livestock buildings.
CAUTIONS:	<p style="text-align: center;">WARNING!</p> <p style="text-align: center;">OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. Causes eye irritation. Vapors can cause flash fire.</p> <p style="text-align: center;">Contains Ethylene Glycol</p> <p>Use only with adequate ventilation. Avoid breathing dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling. Close container after each use. Do not breathe dust, vapors or spray mist. Avoid contact with eyes, skin and clothing.</p> <p>First Aid: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p>WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p>