



CORONADO
P A I N T

SECTION NO. 7
ADS – 803
12 Line
Rev. 02/11

Supreme Collection
Acrylic Semi-Gloss House Paint
12 Line

Type Acrylic	Sheen Semi-Gloss	Theoretical Spread Rate 300 - 400 Sq. Ft. Per Gallon*	Recommended Application Brush, Roller, Pad or Spray	Thinner Clean Water	Clean Up Clean Soapy Water
Dry Time:		Tack Free: 30 Minutes	Recoat: 4 Hours	Full Cure: 7 – 10 Days	

PRODUCT NAME: 12 Line Supreme Collection Acrylic Semi-Gloss House Paint	Acrylic Semi-Gloss House and Trim is formulated to provide long lasting weather, color and gloss retention. The enamel sheen minimizes dirt pickup, so the film stays fresh looking longer. The breathing action of the paint film permits moisture vapor to escape, reducing peeling problems.	
WHERE TO USE:	Wood Hardboard Masonry Metal Galvanized	On exterior siding, trim doors, fascia or shutters. An excellent choice for surfaces where dirt pickup is a concern.

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	The products supported by this data sheet contain a maximum of 150 grams per liter VOC / VOS (1.25 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating.	This product is not currently certified under MPI. This product does meet qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.

SURFACE PREPARATION:	<p>Surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by power washing or hand scrubbing with an abrasive cleanser and water, followed by a clean water rinse. Mildew must be removed by washing the surface with a solution of one part household bleach mixed with six parts water. Rinse well with clean water following wash. Wax should be removed by solvent cleaning. Grease and oil should be cleaned by using CORONADO® Sur-Prep™ I Oil & Grease Emulsifier. Rust must be removed by blasting, hand sanding vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.</p> <p>Priming – (new or bare surfaces): Wood – Use CORONADO® Exterior Primers 8-11 or 5-11. For bleeding wood, such as redwood or cedar, it may be necessary to apply two coats of primer. Masonry – Use CORONADO® Primer/Sealer 43-11 or 48-11. To fill porous block, use 958-11 Latex Block Filler. Ferrous Metal – Use CORONADO® Metal Primers 35-111 or 36-11 Non-Ferrous Metal – Use CORONADO® Grip & Seal Primer 116-11 Galvanized – Use CORONADO® Grip & Seal Primer 116-11</p>
-----------------------------	--

APPLICATION:	Stir product with a circular, lifting motion before you begin to paint. Acrylic Semi-Gloss House and Trim may be applied by brush, spray, pad or roller, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a ¼" or 3/8" nap cover. For spray application, thin with clean water, up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 50° F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
RESIN TYPE:	Acrylic / VA Copolymer
SOLIDS:	Weight: 41.7 ± 1.0% Volume: 30.2 ± 1.0%
WEIGHT PER GALLON:	10.0 lbs.
VISCOSITY:	95 – 100 KU (Krebs Units)
FLASH POINT:	200° F. or greater (TT-P-141, Method 4293)
LIGHT REFLECTANCE:	90% (White or lightest colors)
SPECULAR GLOSS:	40 – 50 units @ 60 degrees
SAG RATING:	Pass 8 mils (Leneta)
REC. FILM THICKNESS:	Wet: 4.0 to 5.4 mils Dry: 1.2 to 1.6 mils
QUALIFICATIONS:	Meets the performance of MIL-P-28578
CAUTIONS:	<p style="text-align: center;">CAUTION! Use only with adequate ventilation.</p> <p>Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.</p> <p>First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p>