



**CORONADO**  
P A I N T

**SECTION NO. 2**  
**ADS – 334**  
**2004 Line**  
**Rev. 10/11**

**Vivid Accents™**  
**Latex Eggshell Enamel**  
**2004 Line**

<b>Type</b> Acrylic	<b>Sheen</b> Eggshell	<b>Theoretical Spread Rate</b> 350 - 450 Sq. Ft. Per Gallon*	<b>Recommended Application</b> Brush, Roller, Pad or Airless Spray	<b>Thinner</b> Clean Water	<b>Clean Up</b> Warm Soapy Water
<b>Dry Time:</b>		<b>Tack Free:</b> 45 Minutes	<b>Recoat:</b> 6 Hours	<b>Full Cure:</b> 10 Days	

<b>PRODUCT NAME:</b> 2004 Line Vivid Accents™ Latex Eggshell Enamel	Vivid Accents™ Latex Eggshell Enamel is formulated to deliver deep, rich, bold and bright colors that are difficult to attain in traditional products. This product has a soft velvet sheen that dries to a durable, smooth finish. It exhibits excellent dirt and stain resistance.	
<b>WHERE TO USE:</b>	<b>Drywall</b> <b>Plaster</b> <b>Wood</b> <b>Metal</b>	Its soft velvet sheen makes it ideal for wood trim or walls throughout residential or commercial structures. Discoloration may be experienced with some colors in high moisture environments. Burnishing may occur with deep, dark colors in frequent use areas.

<b>REGULATORY INFORMATION:</b>	<b>VOC/VOS STATEMENT:</b>	<b>OTC CATEGORY:</b>	<b>MPI / LEED:</b>
	The products supported by this data sheet contain a maximum of 95 grams per liter VOC / VOS (0.79 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating	This product is not currently certified under MPI. This product does meet qualifications for LEED (Leadership in Energy and Environmental Design) projects as a Non-Flat Coating.

<b>SURFACE PREPARATION:</b>	<p>The surface to be painted must be clean and free of dirt, chalk, wax, grease, rust, flaking paint or any other surface contamination that could affect product performance. Dirt and chalk should be removed by scrubbing with warm, soapy water and thoroughly rinsed with clean water. Wax should be removed with a commercial wax stripper or by solvent cleaning to SSPC-SP 1. Grease and oil residue should be cleaned by using Coronado® Sur-Prep™ I Emulsifier. Follow all label directions. Rust must be removed by hand scraping vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Gloss surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.</p> <p><b>PRIMING (New or Bare Surfaces):</b> For best hide when a significant color change is desired, tint primer to the approximate shade of the finish coat.</p> <p><b>Plaster/Drywall</b> – For best results use Latex Primer Sealer 40.11  <b>Wood</b> – For best results use Latex Undercoat 78.11  <b>Ferrous Metal</b> – Use Latex Metal Primer 36.11  <b>Galvanized Metal</b> – Use Grip &amp; Seal™ 116.11 or 116.37, Acrylic Metal Primer 36.11  <b>Masonry</b> – Use Masonry Sealer 48.10 or 48.11</p>
-----------------------------	--

**SECTION NO. 2**  
**ADS-334**  
**2004 Line**

<b>APPLICATION:</b>	<p>Stir product thoroughly before use. This product may be applied by brush, roller or spray techniques, at a rate of application up to 450 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality polyester or nylon/polyester filament brush. For roller application, use a ¼" or ½" nap cover, depending on surface. Thinning is not normally necessary for brush or roller application. For spray application it may be thinned up to 10%, if needed. Certain colors may require multiple, thin coats to achieve full hide. Do not apply if surface or air temperatures are below 50° F.</p> <p><b>IMPORTANT:</b> Examine the contents for proper color, as we cannot be responsible for incorrect color after application. Boxing or inter-mixing containers of different batch numbers, on the same job is highly recommended. Apply product as it comes in the can. The addition of paint additives is not recommended.</p>
<b>*NOTE ON SPREAD RATE:</b>	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
<b>RESIN TYPE:</b>	100% Acrylic
<b>COLORS / TINTING:</b>	This product is available in a -34 Deep Base and a -36 Accent Base, tintable with Universal (glycol-based) colorants.
<b>SOLIDS:</b>	Weight: 43.9 ± 1.0%                      Volume: 32.5 ± 1.0%
<b>WEIGHT PER GALLON:</b>	10.0 lbs.
<b>VISCOSITY:</b>	90 - 95 KU (Krebs Units)
<b>FLASH POINT:</b>	200° F. or greater (TT-P-141, Method 4293)
<b>SPECULAR GLOSS:</b>	20 to 25 units @ 85 degrees
<b>SAG RATING:</b>	Pass 8 mils (Leneta)
<b>REC. FILM THICKNESS:</b>	Wet: 3.6 to 4.6 mils Dry: 1.2 to 1.5 mils
<b>QUALIFICATIONS:</b>	Meets the performance requirements of Federal Spec. TT-P-2119 Class II
<b>CAUTIONS:</b>	<p><b>CAUTION!</b></p> <p><b>Use only with adequate ventilation.</b></p> <p>Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use.</p> <p><b>First Aid:</b> In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p><b>Obtain and read the MSDS prior to using this product.</b> <b>KEEP OUT OF REACH OF CHILDREN</b></p> <p><b>KEEP FROM FREEZING</b></p>