



**CORONADO**  
P A I N T

**SECTION NO. 1**  
**ADS-213**  
**CERAMAGARD®**  
**2102 Line**  
**Rev. 10/11**

Complementary Coatings Corp. · 101 Paragon Drive · Montvale, NJ · 800-225-5554 · FAX 888-248-2143

**CERAMAGARD® 100% ACRYLIC**  
**Interior Matte Flat Finish – 2102 Line**

Type	Sheen	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Styrene Acrylic	Flat	300 - 400 Sq. Ft. Per Gallon*	Brush, Pad, Roller or Spray	Water	Soapy Water
<b>Dry Time:</b>		<b>Tack Free:</b> 30 Minutes	<b>Recoat:</b> 4 Hours	<b>Full Cure:</b> 10 Days	

<b>PRODUCT NAME:</b> <b>2102 Line</b> <b>CeramaGard®</b> <b>100% Acrylic Interior</b> <b>Matte Flat Finish</b>	<p>CORONADO® - CERAMAGARD® - Matte Flat Finish utilizes the latest in paint formulating technology to produce a stain-proof yet aesthetically pleasing interior wall coating. CERAMAGARD® finishes contain hard, ceramic micro-spheres. These together with the latest generation acrylic resins make the cured film impervious to household stains, which can be readily removed with common household cleansers.</p> <p>Low in odor, quick drying and absolutely spatterless, CERAMAGARD® - Matte Flat Finish flows naturally and smoothly and can be applied easily by the professional as well as the occasional painter. It imparts a truly flat finish, yet will withstand repeated scrubbing. CERAMAGARD® - Matte Flat is available in an unlimited array colors.</p>	
<b>WHERE TO USE:</b>	<b>Drywall</b> <b>Plaster</b> <b>Masonry</b> <b>Metal</b> <b>Wood</b>	<p>CERAMAGARD® - Matte Flat Finish can be used on virtually all interior surfaces where a durable, flat finish is desired. It is recommended for use in residential as well as institutional and commercial environments. Typical applications would be on walls, woodwork, ceilings, ductwork, partitions in homes, offices, schools, hospitals, shopping centers, common areas, etc.</p>

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	<p>The products supported by this data sheet contain a maximum of 100 grams per liter VOC / VOS (0.83 lbs/gal.) excluding water &amp; exempt solvents.</p>	<p>This product is compliant under the Ozone Transport Commission regulations as a Flat Coating</p>	<p>This product is not currently certified under MPI. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.</p>

<b>SURFACE PREPARATION:</b>	<p>Surface to be painted must be clean and free of dirt, wax, rust, mildew, grease or loose, flaking paint. Patch all cracks, chips, nail holes and gouges using an appropriate patching compound. Dirt and chalk should be removed by scrubbing with warm, soapy water and thoroughly rinsed with clean water. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using CORONADO® Sur-Prep™ I. Rust must be removed by scrubbing with a solution of one (1) part household bleach and three (3) parts water. Rinse thoroughly with clean water and allow it to dry. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate or patches should be spot primed with the appropriate primer.</p>
<b>PRIMING:</b>	<p><b>New or Bare Surfaces:</b>  <b>Plaster/Drywall</b> - For best results use CERAMAGARD® Multi-Purpose Primer/Sealer 2110-11; however, two un-thinned coats of CERAMAGARD® Matte Flat Finish will provide satisfactory results.  <b>Wood</b> - Use CERAMAGARD® Multi-Purpose Primer/Sealer 2110-11.  <b>Masonry</b> - Use CORONADO® Masonry Sealer 48-11.  <b>Ferrous Metal</b> - Use CORONADO® Acrylic Metal Primer 36-11.  <b>Galvanized/Aluminum</b> - Use CERAMAGARD® Multi-Purpose Primer/Sealer 2110-11.</p>

**SECTION No. 1**  
**ADS-213**  
**2102 Line**

<b>APPLICATION:</b>	Stir product with a circular, lifting motion before you begin to paint. CERAMAGARD® - Matte Flat Finish may be applied by brush, roller, pad or spray. For roller application use a 3/8" or 1/2" nap cover for smooth surfaces, a 3/4" nap cover for semi-rough surfaces and a 1" nap cover for rough surfaces. For best brush application results use a quality brush with a synthetic filament. If applying by airless spray, a .017 to .021 size tip will produce the best results. For spray application, CERAMAGARD® - Matte Flat Finish may be thinned with clean water, up to 15% if necessary. The addition of paint additives is not recommended. Apply when surface, ambient and material temperatures are over 50° F.
<b>*NOTE ON SPREAD RATE:</b>	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
<b>RESIN TYPE:</b>	Styrene Acrylic
<b>COLORS / TINTING:</b>	Available in White, Pastel Base & Tint Base, tintable with Universal (glycol-based) colorants.
<b>SOLIDS:</b>	Wt: 62.6 ± 1.0%      Vol.: 45.4 ± 1.0%
<b>WEIGHT PER GALLON:</b>	12.2 lbs.
<b>VISCOSITY:</b>	90 - 95 KU (Krebs Units)
<b>FLASH POINT:</b>	200° F. and greater (TT-P-141, Method 4293)
<b>SPECULAR GLOSS:</b>	0.8 - 1.0 units @ 85
<b>SAG RATING:</b>	Pass 9 mils (Leneta)
<b>REC. FILM THICKNESS:</b>	Wet: 4.0 to 5.3 mils Dry: 1.8 to 2.4 mils
<b>LIGHT REFLECTANCE:</b>	89%
<b>TEST DATA:</b>	
<b>Scrubability:</b>	ASTM-D2486 - 1,000 Cycles
<b>Flow &amp; Leveling:</b>	ASTM-D4062-9
<b>QUALIFICATIONS:</b>	Meets the performance requirements of TT-P-2119, Class I
<b>CAUTIONS:</b>	<p><b>WARNING!</b> HARMFUL IF INHALED. Keep away from heat and flame.</p> <p><b>Use only with adequate ventilation.</b> Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use. Wash thoroughly after handling.</p> <p>If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.</p> <p><b>Obtain and read the MSDS prior to using this product.</b> <b>KEEP OUT OF REACH OF CHILDREN</b></p>
<b>LIFETIME WARRANTY:</b>	<p><b>SATISFACTION GUARANTEED:</b></p> <p>Your satisfaction is guaranteed for as long as you live in your home when you use CERAMAGARD® Ultra Premium Finishes. This warranty covers paint that is applied according to label directions on a properly prepared surface. If this paint fails to perform as warranted, return any unused portion along with your receipt in exchange for your money back or an equivalent amount of new paint. This warranty excludes failure due to structural defects, improper surface preparation or failure of previously applied coatings.</p>