



CORONADO
P A I N T

SECTION NO. 1
ADS -203
28 LINE
Rev. 05/11



Super Kote™ 5000
Vinyl Latex Flat Wall
28 Line

Type Vinyl Latex	Sheen Flat	Theoretical Spread Rate 300 – 400 Sq. Ft. Per Gallon*	Recommended Application Brush, Roller Pad or Airless Spray	Thinner Clean Water	Clean Up Warm Soapy Water
Dry Time:		Tack Free: 30 Minutes	Recoat: 4 Hours	Full Cure: 10 Days	

PRODUCT NAME: 28 Line Super Kote 5000™ Vinyl Latex Flat Wall Paint	Super Kote 5000™ Vinyl Latex Flat Wall is designed especially for the journeyman applicator to cover most surfaces in one coat when applied at a spread rate not to exceed 400 square feet per gallon. This vinyl latex flat is spatterless and exhibits excellent touch-up characteristics.
WHERE TO USE:	Drywall Plaster Wood Metal Cement Block Stucco For application as a finish coat on interior drywall, plaster, woods, metal and block. Use on walls, ceilings and trim. Also suitable for exterior concrete or stucco vertical surfaces in southern climates where below freezing temperatures are rare.

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	The products supported by this data sheet contain a maximum of 50 grams per liter VOC / VOS (0.41 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Flat Coating.	This product is not currently certified under MPI. This product does meet qualifications for LEED (Leadership in Energy and Environmental Design) projects as a flat coating.

SURFACE PREPARATION:	<p>New Work: The surface to be coated must be clean and free of dust, mildew, grease, wax, chalk, rust, oil and bleeding stains.</p> <p>Priming: Drywall – Self priming, but for best results use 40-11 Latex Primer Sealer Plaster – Self priming, but for best results use 40-11 Latex Primer Sealer Wood – Alkyd Primer Undercoat 37-11 or Latex Enamel Undercoat 78-11 Ferrous Metal – Rust Inhibiting Metal Primer such as 35-11, 35-147, 35-153 or 36-11 Non-Ferrous Metal – Use Grip & Seal™ 116-11 Galvanized – Use Grip & Seal™ 116-11 Masonry – Use Pigmented Masonry Sealer 48-11 or 116-11</p> <p>Repaint Work: On previously painted surfaces in good repair, no priming is generally necessary. Mildew must be removed by scrubbing with a solution of one part household bleach and three parts water. Rinse well with clean water and allow it to dry thoroughly before painting. On glossy surfaces, remove the sheen with sandpaper or steel wool. Patch holes or cracks with appropriate filler. Spot prime bare areas with indicated primer. Remove any oil, chalk, dirt, wax or dust prior to recoating. Any loose or flaking paint should be removed and the edges feather sanded to produce a smooth, uniform surface.</p>
-----------------------------	--

APPLICATION:	<p>Stir product thoroughly with a circular, lifting motion before you begin to paint. This Vinyl Latex Flat Wall Paint may be applied by brush, roller, pad or spray techniques, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results use a quality synthetic filament brush. For roller application use a 3/8" nap cover for smooth surfaces, a 1/2" nap cover for semi-rough surfaces, and a 3/4" to 1" nap cover for rough surfaces. Thinning is not recommended; if necessary, use clean water sparingly. Apply when surface temperature is above 50° F. Do not apply directly over chalky surfaces or bleeding stains.</p> <p>Airless Spray – Tip size and atomization pressures will vary with type of equipment, viscosity & temperature. An orifice of 17 to 21 thousandths will provide the most satisfactory spray pattern.</p>
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
RESIN TYPE:	Vinyl Acrylic
SOLIDS:	Weight: 50.8 ± 1.0% Volume: 32.1 ± 1.0%
WEIGHT PER GALLON:	11.6 lbs.
VISCOSITY:	105 to 110 KU (Krebs Units)
FLASH POINT:	200° F. or greater (TT-P-141, Method 4293)
SPECULAR GLOSS:	1 – 2 units @ 85 Degrees
SAG RATING:	Pass 8 mils (Leneta)
REC. FILM THICKNESS:	Wet: 4.0 to 5.3 mils Dry: 1.3 to 1.7 mils
LIGHT REFLECTANCE:	91% White
QUALIFICATIONS:	Meets the performance requirements of TT-P-29.
CAUTIONS:	<p style="text-align: center;">WARNING!</p> <p>HARMFUL IF INHALED. OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. Cancer hazard. Contains Crystalline Silica which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated by sanding surfaces or spray mist. Overexposure may cause lung and kidney damage. Causes eye irritation.</p> <p>Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate properly fitted respirator (NIOSH approved) during and after application. Avoid exposure to dust by wearing an appropriate (NIOSH approved) particulate respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.</p> <p>First Aid: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p>WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product.</p> <p style="text-align: center;">KEEP OUT OF REACH OF CHILDREN</p>