



CORONADO
P A I N T

SECTION NO. 2
ADS – 306
32 LINE
Rev. 05/11



Super Kote™ 5000
Acrylic Semi-Gloss Enamel
32 Line

Type Vinyl Acetate/Acrylic	Sheen Semi-Gloss	Theoretical Spread Rate 300 - 400 Sq. Ft. Per Gallon*	Recommended Application Brush, Roller, Pad or Spray	Thinner Clean Water	Clean Up Warm Soapy Water
Dry Time:		Tack Free: 30 Minutes	Recoat: 4 Hours	Full Cure: 7-10 Days	

PRODUCT NAME: 32 Line Super Kote 5000™ Acrylic Semi-Gloss Enamel	Super Kote 5000™ Acrylic Semi-Gloss Enamel is suited for wall and trim applications in kitchens, bathrooms, family rooms, hallways and children's bedrooms where routine cleaning is needed. Fast dry, low odor and pleasant semi-gloss sheen make it an ideal finish for residential or commercial jobs.
WHERE TO USE:	<p>Drywall Plaster Wood Metal Masonry Stucco</p> <p>Super Kote 5000™ Acrylic Semi-Gloss Enamel can be applied to walls, woodwork, trim, paneling, doors or dados. It is a good choice for interior bedrooms, family rooms, hallways, recreation rooms and commercial or rental properties.</p> <p>Suitable for exterior stucco and masonry in southern climates where freezing temperatures are rare.</p>

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	The products supported by this data sheet contain a maximum of 100 grams per liter VOC / VOS (0.83 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating.	This product is certified under MPI #54. This product does meet qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.

SURFACE PREPARATION:	<p>Surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Mildew must be removed by scrubbing with a solution of one part household bleach and three parts water. Rinse well with clean water and allow it to dry thoroughly before painting. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using CORONADO® Sur-Prep™ I Oil & Grease Emulsifier. Rust must be removed by hand sanding or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to ensure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.</p> <p>PRIMING (New or Bare Surfaces): Plaster/Drywall – For best results use CORONADO® Primer Sealer 40-11 or 78-11; however, two coats of Super Kote 5000™ Acrylic Semi-Gloss Enamel will provide satisfactory results. Wood – Use CORONADO® Undercoat 37-11 or 78-11 Smooth Masonry – Use CORONADO® Masonry Sealer 48-11 Block – Use CORONADO® 958-11 Block Filler Ferrous Metal – Use CORONADO® Metal Primer 35-111, 35-147, 35-153 or 36-11 Non-Ferrous Metal – Use 116-11 Grip & Seal™ Galvanized – Use 116-11 Grip & Seal™</p>
-----------------------------	--

APPLICATION:	Stir product with a circular, lifting motion before you begin to paint. Super Kote 5000™ Acrylic Semi-Gloss Enamel may be applied by brush, roller, pad or spray techniques, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic bristle brush. For roller application, use a ¼" nap cover for smooth surfaces, a 3/8" or ½" nap cover for semi-rough surfaces and a ¾" nap cover for rough surfaces. Thinning is not normally necessary, if required use water sparingly. For spray application Acrylic Semi-Gloss Enamel may be thinned with clean water, up to 15% reduction if necessary. Apply when surface temperature is above 50° F.
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
RESIN TYPE:	Vinyl Acetate/Acrylic
SOLIDS:	Weight: 45.8 ± 1.0% Volume: 32.4 ± 1.0%
WEIGHT PER GALLON:	10.3 lbs.
VISCOSITY:	95 – 100 (Krebs Units)
FLASH POINT:	200° F. or greater (TT-P-141, Method 4293)
SPECULAR GLOSS:	45 – 55 units @ 60 Degrees
SAG RATING:	Pass 8 mils (Leneta)
REC. FILM THICKNESS:	Wet: 4.0 to 5.3 mils Dry: 1.3 to 1.8 mils
LIGHT REFLECTANCE:	92% (White or lightest colors)
QUALIFICATIONS:	Meets the performance requirements of TT-P-1511, Type I Certified under MPI #54
CAUTIONS:	<p style="text-align: center;">WARNING!</p> <p style="text-align: center;">OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. Causes eye irritation.</p> <p>Use only with adequate ventilation. Avoid breathing dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling.</p> <p>First Aid: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p> <p style="text-align: center;">KEEP FROM FREEZING</p>