



Products environmentally
engineered to improve
air quality and product safety



CORONADO
PAINT

32 Series

SuperKote® 5000
Semi-Gloss Enamel

Interior Coatings

| Health & Environmental Standards | ASTM Test Standard | Green Seal GS-11 | MPI Green GPS-1 |  LEEDS Standards |  LOW VOC |
|------------------------------------------------|--------------------|----------------------|---------------------|-----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| VOC Content- <i>Volatile Organic Compounds</i> | ASTM-6886-03 | 100 grams/liter max. | 100 grams/liter | 100 grams/liter | 100 grams/liter max. ✓ |
| Organic Dichlorobenzenes | | None allowed | None allowed | None allowed | 0% None Allowed ✓ |
| Formaldehyde Donors | | None allowed | None allowed | None allowed | 0% None Allowed ✓ |
| Heavy Metals | | None allowed | None allowed | None allowed | 0% None Allowed ✓ |
| Volatile Aromatic Compounds | | .05% maximum by wt. | .05% maximum by wt. | .05% maximum by wt. | .02% maximum by wt. ✓ |
| Butyl Tin Compounds | | None allowed | None allowed | None allowed | 0% None Allowed ✓ |
| Silica (<i>crystalline</i>) | | | | | .01% maximum by wt. ✓ |
| Fibrous Talc | | | | | .02% maximum by wt. ✓ |
| Ethylene Glycol | | | | | 0% None Allowed ✓ |

| Performance Standards Commercial Lines | | | | | |
|----------------------------------------|----------------|------------------------------|--|---------------|------------------------------|
| Hiding Power | ASTM-D2805-96a | 95% Contrast Ratio or better | | Not specified | 97% Contrast Ratio or better |
| Flow & Leveling | ASTM-D7073-05 | 6 rating or better | | Not specified | 6 rating or better |
| Spatter Resistance | ASTM-D7073-05 | 6 rating or better | | Not specified | 6 rating or better |
| Foaming | ASTM-D7073-05 | 6 rating or better | | Not specified | 6 rating or better |
| | | | | | |

✓ Meets or exceeds comparative environmental standards

This data chart is provided for comparison purposes only. Coronado products are formulated to strict regulatory compliance and exceed all EPA national standards. Products formulated to the Green Mark™ standards often exceed other industry environmental standards. References to Green Seal GS-11 is for comparison purposes only and does not imply that Coronado products are certified by the Green Seal organization. Products referenced on this data sheet will meet or exceed the requirements of the United States Green Building Council's LEEDS for new construction and maintenance projects. Many Coronado products are certified by the Master Painters Institute (MPI) for performance. The MPI-1 green standard is used on this chart for reference purposes only.