



CRYLICOTE® GOLD COLLECTION
100% ACRYLIC DARK BASE HOUSE PAINT PRIMER
410-1129

Type	Sheen	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Acrylic	Flat	300 – 400 Sq. Ft. Per Gallon*	Brush, Roller, Pad or Spray	Clean Water	Warm Soapy Water
Dry Time:	Tack Free: 30 Minutes	Recoat:	4 Hours	Full Cure :	7 – 10 Days

PRODUCT NAME: 410-1129 Crylicote® Gold Collection Acrylic Dark Base House Paint Primer	An acrylic latex primer for use over wood, masonry and previously painted surfaces. Intended for use under deep colored finishes. It seals new cedar and redwood; dries dust and bug free in thirty minutes. It is water thinned, blister and peel resistant and high hiding. It may be used on unpainted galvanized metal as well as masonry and wood surfaces. This product is intended to be tinted to improve system hiding. See tinting recommendations below.	
WHERE TO USE:	Wood Masonry Brick Cement/Asbestos Hardboard Galvanized	On exterior siding, trim, fascia, fences and gutters. Will seal staining types of woods such as cedar and redwood (in two coats). May be top-coated with latex oil finishes.

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	The product supported by this data sheet contains a maximum of 150 grams per liter VOC / VOS (1.25 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Primer/Sealer/Undercoater.	This product is not currently certified under MPI. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.

SURFACE PREPARATION:	The surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose flaking paint. Dirt and chalk should be removed by power washing or hand scrubbing with TSP (or equivalent) and water, followed by a clean water rinse. Wax should be removed by solvent cleaning. Grease and oil should be cleaned using CORONADO® Sur-Prep™ I Oil & Grease Emulsifer. Rust must be removed by blasting, had sanding vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust prior to paint application.
-----------------------------	---

APPLICATION:	Stir product with a circular, lifting motion before you begin to paint. Crylicote® Acrylic Dark Base House Paint Primer may be applied by brush, roller, pad or spray at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush results, use a quality synthetic filament brush; for roller application, use a 3/8" or 1/2" nap cover for rough surfaces; for spray application, this product may be thinned with clean water up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 35°F or if surface or air temperatures will drop below 35°F within 8 hours of application. Do not apply to a hot surface or if rain is threatening.
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
RESIN TYPE:	100% Acrylic
VOLUME SOLIDS:	Weight: 46.2 ± 1.0% Volume: 34.5 ± 1.0%
WEIGHT PER GALLON:	10.1 lbs.
VISCOSITY:	90 - 95 KU (Krebs Units)
FLASH POINT:	200°F. or over (TT-P-141 Method 4293)
SPECULAR GLOSS:	5 – 10 units @ 85 Degrees
SAG RATING:	Pass 6 mils (Leneta)
WET FILM THICKNESS:	4.0 to 5.3 Mils
DRY FILM THICKNESS:	1.4 to 1.9 Mils
TINTING:	Tint with Universal (glycol based) colorants up to 8 ounces per gallon.
QUALIFICATIONS:	Meets the performance requirements of TT-P-1984
CAUTIONS:	<p style="text-align: center;">WARNING!</p> <p style="text-align: center;">HARMFUL IF INHALED. OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. Contains Crystalline Silica which can cause cancer. Risk of cancer depends on duration and level of exposure.</p> <p>Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.</p> <p>First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.</p> <p>WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p>