



**CORONADO**  
P A I N T

**SECTION NO. 1**  
**ADS -2**  
**62 LINE**  
**Rev. 06/11**

**FINAL TOUCH™**  
**Interior Latex Flat Ultra Touch Up Wall Paint**  
**62 Line**

<b>Type</b> Vinyl Acrylic	<b>Sheen</b> Flat	<b>Theoretical Spread Rate</b> 300 to 400 Sq. Ft. per gallon*	<b>Recommended Application</b> Brush, Roller, Pad or Spray	<b>Thinner</b> Clean Water	<b>Clean Up</b> Warm Soapy Water
<b>Dry Time:</b>		<b>Tack Free:</b> 30 Min.	<b>Recoat:</b> 4 Hrs.	<b>Full Cure:</b> 10 Days	

<b>PRODUCT NAME:</b> 62 Line Final Touch™ Interior Latex Flat	FinalTouch™ is formulated to provide perfect touch-up and final finishing for all interior new construction wall surfaces. After spray and back-roll of your final finish coat, FinalTouch™ is designed to feather smoothly with a fine nap roller to provide invisible touch-ups.							
<b>WHERE TO USE:</b>	<table border="0"> <tr> <td><b>Drywall</b></td> <td><b>Plaster</b></td> <td rowspan="4">An ideal flat coating to be used for new construction as well as general maintenance, apartments and the budget minded consumers. <b>NOTE:</b> Not for use in high abuse areas.</td> </tr> <tr> <td><b>Wood</b></td> <td><b>Metal</b></td> </tr> <tr> <td><b>Masonry Block</b></td> <td><b>Cement Stucco</b></td> </tr> </table>	<b>Drywall</b>	<b>Plaster</b>	An ideal flat coating to be used for new construction as well as general maintenance, apartments and the budget minded consumers. <b>NOTE:</b> Not for use in high abuse areas.	<b>Wood</b>	<b>Metal</b>	<b>Masonry Block</b>	<b>Cement Stucco</b>
<b>Drywall</b>	<b>Plaster</b>	An ideal flat coating to be used for new construction as well as general maintenance, apartments and the budget minded consumers. <b>NOTE:</b> Not for use in high abuse areas.						
<b>Wood</b>	<b>Metal</b>							
<b>Masonry Block</b>	<b>Cement Stucco</b>							

<b>REGULATORY INFORMATION:</b>	<b>VOC/VOS STATEMENT:</b>	<b>OTC CATEGORY:</b>	<b>MPI / LEED:</b>
	The products supported by this data sheet contain a maximum of 90 grams per liter VOC / VOS (0.75 lbs./gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Flat Coating.	This product is not currently certified under MPI. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.

<b>SURFACE PREPARATION:</b>	<p>Surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Mildew must be removed by scrubbing with a solution of one part household bleach and three parts water. Rinse well with clean water and allow it to dry thoroughly before painting. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using CORONADO® Sur-Prep™ I Oil &amp; Grease Emulsifier. Rust must be removed by hand sanding or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.</p> <p><b>PRIMING (New or Bare Surfaces):</b>  <b>Plaster/Drywall</b> – For best results use CORONADO® Primer Sealer 40-11 or 948-11. However, two un-thinned coats of Final Touch™ Interior Latex Flat will provide satisfactory results.  <b>Wood</b> – Use CORONADO® Undercoat 37-11 or 78-11  <b>Smooth Masonry</b> – Use CORONADO® Masonry Sealer 48-11  <b>Block</b> – Use CORONADO® Block Filler 958-11  <b>Ferrous Metal</b> – Use CORONADO® Metal Primer 35-111, 35-147, 35-153 or 36-11  <b>Non-Ferrous Metal</b> – Use CORONADO® Grip &amp; Seal 116-11  <b>Galvanized</b> – Use CORONADO® Grip &amp; Seal 116-11</p>
-----------------------------	--

**SECTION NO. 1**  
**ADS -2**  
**62 LINE**

<b>APPLICATION:</b>	<p>Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout.</p> <p><b>Roller</b> – 3/8" nap, depending on surface texture</p> <p><b>Brush</b> – Nylon or polyester filament</p> <p><b>Airless Spray</b> – Tip size and atomization pressure will vary with type of equipment, viscosity and temperature. Normally a tip size of .017 @ 2000-2500 psi will provide the most satisfactory spray pattern. If necessary product may be thinned up to 10% with clean water for spray application.</p> <p>Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains. Apply when temperature is above 50° F and in humidity less than 85%.</p>
<b>* NOTE ON SPREAD RATE:</b>	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
<b>RESIN TYPE:</b>	Vinyl Acrylic Polymer
<b>COLORS / TINTING:</b>	FinalTouch™ is available in -1 White, -32 Pastel Base and -33 Tint Base. Bases can be tinted with Universal (glycol based) colorant.
<b>SOLIDS:</b>	Weight: 51.5 ± 1.0%                      Volume: 32.9 ± 1.0%
<b>WEIGHT PER GALLON:</b>	11.6 lbs.
<b>VISCOSITY:</b>	108 – 113 KU (Krebs Units)
<b>FLASH POINT:</b>	200°F. or greater (TT-P-141, Method 4293)
<b>SPECULAR GLOSS:</b>	0.5 – 1.0 units @ 85 Degrees
<b>SAG RATING:</b>	Pass 8 mils (Leneta)
<b>REC. FILM THICKNESS:</b>	Wet: 4.0 to 5.4 mils
	Dry: 1.3 to 1.8 mils
<b>LIGHT REFLECTANCE:</b>	90% (White or Lightest Colors)
<b>CAUTIONS:</b>	<p style="text-align: center;"><b>CAUTION!</b></p> <p style="text-align: center;"><b>Use only with adequate ventilation.</b></p> <p>Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.</p> <p style="text-align: center;">Contains Ethylene Glycol &amp; Crystalline Silica.</p> <p><b>First Aid:</b> In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.</p> <p style="text-align: center;">If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p><b>WARNING:</b> This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;"><b>Obtain and read the MSDS prior to using this product.</b></p> <p style="text-align: center;"><b>KEEP OUT OF REACH OF CHILDREN</b></p>