



**CORONADO**  
P A I N T

**SECTION NO. 7**  
**ADS – 801**  
**8 Line**  
**Rev. 02/11**

**Supreme Collection  
Acrylic Latex House Paint  
8 Line**

<b>Type</b> Acrylic	<b>Sheen</b> Flat	<b>Theoretical Spread Rate</b> 300 - 400 Sq. Ft. Per Gallon*	<b>Recommended Application</b> Brush, Roller, Pad or Spray	<b>Thinner</b> Clean Water	<b>Clean Up</b> Warm Soapy Water
<b>Dry Time:</b>		<b>Tack Free:</b> 30 Minutes	<b>Recoat:</b> 4 Hours	<b>Full Cure:</b> 7 – 10 Days	

<b>PRODUCT NAME:</b> 8 Line Supreme Collection Acrylic Latex House Paint	This Acrylic Latex House Paint is designed for service over new or previously painted surfaces in good condition. It is formulated to cover most surfaces in one coat when applied at the rate of four hundred square feet per gallon. Acrylic Latex House Paint dries dust and bug free in thirty minutes. Provides a durable and protective finish on any properly primed and prepared exterior surface.	
<b>WHERE TO USE:</b>	<b>Wood</b> <b>Hardboard</b> <b>Masonry</b> <b>Metal</b> <b>Galvanized</b>	On exterior siding, foundations, fascia, shutters or retaining walls.

<b>REGULATORY INFORMATION:</b>	<b>VOC/VOS STATEMENT:</b>	<b>OTC CATEGORY:</b>	<b>MPI / LEED:</b>
	The products supported by this data sheet contain a maximum of 100 grams per liter VOC / VOS (0.83 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Flat Coating.	This product is certified under MPI #10. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.

<b>SURFACE PREPARATION:</b>	<p>Surface to be primed must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by power washing or hand scrubbing with an abrasive cleanser and water, followed by a clean water rinse. Mildew must be removed by washing the surface with a solution of one part household bleach mixed with six parts water. Rinse well with clean water following wash. Wax should be removed by solvent cleaning. Grease and oil should be cleaned by using CORONADO® Sur-Prep™ I Oil &amp; Grease Emulsifier. Rust must be removed by blasting, hand sanding vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.</p> <p><b>Priming – (New or bare surfaces):</b>  <b>Wood</b> – Use CORONADO® Exterior Latex Primers 410-11, 8-11, or 5-11. For bleeding wood, such as redwood or cedar, it may be necessary to apply two coats of primer.  <b>Masonry</b> – Use CORONADO® Primer/Sealer 48-11. To fill porous block, use 958-11 Latex Block Filler.  <b>Ferrous Metal</b> – Use CORONADO® Metal Primers 35-111 or 36-11  <b>Non-Ferrous Metal</b> – Use CORONADO® Grip &amp; Seal Primer 116-11  <b>Galvanized</b> – Use CORONADO® Grip &amp; Seal Primer 116-11</p>
-----------------------------	---

<b>APPLICATION:</b>	Stir product with a circular, lifting motion before you begin to paint. May be applied by brush, spray, pad or roller, at a rate of up to 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application, use a 3/8" to 1 1/2" nap cover depending on surface texture. For spray application, thin with clean water, up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 50° F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.
<b>*NOTE ON SPREAD RATE:</b>	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
<b>RESIN TYPE:</b>	Acrylic / VA Copolymer
<b>SOLIDS:</b>	Weight: 48.5 ± 1.0 % Volume: 32.0 ± 1.0%
<b>WEIGHT PER GALLON:</b>	11.1 lbs.
<b>VISCOSITY:</b>	92 – 97 KU (Krebs Units)
<b>FLASH POINT:</b>	200° F. or greater (TT-P-141, Method 4293)
<b>SPECULAR GLOSS:</b>	2 – 4 units @ 85 degrees
<b>LIGHT REFLECTANCE:</b>	89% (White or Lightest Colors)
<b>SAG RATING:</b>	Pass 8 mils (Leneta)
<b>REC. FILM THICKNESS:</b>	Wet: 4.0 to 5.3 mils Dry: 1.3 to 1.7 mils
<b>QUALIFICATIONS:</b>	This product meets the performance requirements of TT-P-19D, TT-P-96 Type I, II & III and TT-P-1510 Meets the performance requirements of Federal Specification A-A-3183 Certified under MPI #10
<b>CAUTIONS:</b>	<p style="text-align: center;"><b>WARNING!</b> OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. <b>Contains:</b> Ethylene Glycol. Causes eye irritation.</p> <p><b>Use only with adequate ventilation.</b> Avoid breathing dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling.</p> <p><b>First Aid:</b> In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p><b>WARNING:</b> This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;"><b>Obtain and read the MSDS prior to using this product.</b> <b>KEEP OUT OF REACH OF CHILDREN</b></p>