



**Seal & Finish Clear**  
**100% Acrylic Coating**  
**82-10**

Type	Sheen	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Acrylic	Gloss See Below	300-500 Sq. Ft. Per Gallon*	Brush, Roller or Spray	Clean Water	Warm Soapy Water
<b>Dry Time:</b>		<b>Tack Free:</b> 1 – 2 Hrs.	<b>Recoat:</b> 4 Hrs.	<b>Full Cure:</b> 7 – 10 Days	

<b>PRODUCT NAME:</b> 82-10 Seal & Finish Clear 100% Acrylic Coating	This clear, water thinned sealer offers deep penetration into stucco, concrete and masonry surfaces. It will form a tough invisible film that repels water and helps reduce spalling and dusting. Will seal and refurbish a paint film that is showing signs of fading due to oxidation. Produces maximum intercoat adhesion between paint films. For interior or exterior use. Not designed as a clear finish for wood.	
<b>WHERE TO USE:</b>	<b>Concrete</b> <b>Stucco</b> <b>Paint Additive</b> <b>Aluminum Siding</b> <b>Restorer</b>	On interior or exterior surfaces such as walls, floors and existing paint finishes. Add to latex products for increased wet edge, adhesion, scrubability, penetration, ease of application, additional gloss or additional spread rate. Use over properly prepared aluminum siding to restore much of the original lustre and brilliance.
<b>SURFACE PREPARATION:</b>	Surface must be clean and free of all oil, grease, excessive chalk, efflorescence, dust and dirt. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Neutralize efflorescence by acid etching and mold or mildew by scrubbing thoroughly with a solution of one part household bleach, one part T.S.P. and three parts warm water. Rinse well with clean water following etch or wash.	
<b>APPLICATION:</b>	<p>Stir product thoroughly prior to painting. This clear sealer is a concentrate and may be reduced as much as 1 to 1 to achieve desirable penetration and gloss level. Apply a coat by brush, roller or spray at a spread rate of 300 to 500 square feet per gallon. Take care to insure 100% coverage of the surface. Do not use outside if temperatures are below 50° F or if rain is threatening. Test a small area to insure desired results when applying over previously coated surfaces.</p> <p>Directions for use, as an additive, compatibility with the latex product you wish to add it to is very important. The amount to be added will vary with each product and with the desired results. Reducing with water may be desirable when adding to some products.</p>	
<b>*NOTE ON SPREAD RATE:</b>	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.	
<b>RESIN TYPE:</b>	Acrylic	
<b>SOLIDS:</b>	Weight: 20.9 ± 1.0% Volume: 19.0 ± 1.0%	
<b>WEIGHT PER GALLON:</b>	8.5 lbs.	
<b>VISCOSITY:</b>	60 – 65 KU (Krebs Units)	
<b>FLASH POINT:</b>	200° F. or greater (TT-P-141, Method 4293)	
<b>SPECULAR GLOSS:</b>	60+ units @ 60 degrees	

<b>SAG RATING:</b>	Pass 6 mils (Leneta)
<b>REC. FILM THICKNESS:</b>	Wet: 3.2 to 5.3 mils
	Dry: 0.6 to 1.0 mils
<b>CAUTIONS:</b>	<p style="text-align: center;"><b>WARNING!</b> OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE. <b>Contains:</b> Ethylene Glycol. Causes eye irritation.</p> <p><b>Use only with adequate ventilation.</b> Avoid breathing dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling.</p> <p><b>First Aid:</b> In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p><b>WARNING:</b> This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;"><b>Obtain and read the MSDS prior to using this product.</b> <b>KEEP OUT OF REACH OF CHILDREN</b></p>
<b>VOC/VOS STATEMENT:</b>	This product contains a maximum of 180 grams VOC/VOS per liter of coating. (1.5 pounds per gallon)
<b>OTC CATEGORY:</b>	This product is compliant under the Ozone Transport Commission regulations as a Waterproofing Sealer in all container sizes.

02/09