



IMA-906
Coroguard™ Graffiti Remover
827-600
Rev. 05/09

Coronado Industrial Coatings - 308 Old County Road - Edgewater, Florida 32132 - 800-883-4193 - FAX 800-394-9022

COROGUARD™ GRAFFITI REMOVER 827-600

GENERAL PROPERTIES: Coroguard™ Graffiti Remover is a special blend of solvents in a bodied paste form for use as a companion product to Coronado's Anti-Graffiti System. Coroguard™ Graffiti Remover will successfully remove most spray paint, magic marker, permanent marker, ink, crayon, lip stick, etc. without damaging gloss, color or film integrity of the paint finish.

RECOMMENDED FOR: Removing graffiti from surfaces coated with Coronado's system; interior-exterior hallways, retaining walls, buildings, fences, equipment, public restrooms or anywhere a graffiti problem exists.

APPLICATION: Apply Coroguard™ Graffiti Remover liberally by brush or roller over the effected areas and allow it to work for five minutes. Using a stiff bristled brush, scrub the areas thoroughly and rinse away with clean water; repeat the process if necessary. Work in areas approximately three feet by three feet, removing all graffiti before moving on to the next area. One gallon of 827-600 will effectively treat about 150 square feet of surface area.

FLASH POINT: 60° F (Seta)

DISPOSAL INFORMATION: Dispose of used remover and paint residue per local, state and regional regulations. Refer to OSHA Form 20 for additional disposal information.

WARNING!

COMBUSTIBLE LIQUID AND VAPOR. FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED.
Causes eye, nose, throat and skin irritation. Harmful if swallowed. **Contains** Methyl Isobutyl Ketone and Propylene Glycol m-Methyl Ether.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks and flame. Vapors can cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

DANGER – Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container.

Obtain and read the MSDS prior to using this product.
KEEP OUT OF REACH OF CHILDREN

INGREDIENTS & CAS #: Methyl Isobutyl Ketone #108.10.1 – Propylene Glycol m-Methyl Ether #107.98.2 – Amorphous Fumed silica #112945.52.5 – Hydrated Magnesium Aluminum Silicate #12174.11.7 – N-Dimethyle Thanolamine #108.01.0

WEIGHT PER GALLON: 7.4 lbs.

SOLIDS: 4.7% (Wt.) 2.8 ± 1.0% (Vol.)

VOC/VOS STATEMENT: This product contains a maximum of 845 grams VOC/VOS per liter of coating.
(7.0 pounds per gallon)

OTC CATEGORY: This product is not regulated under the OTC regulations.

