



CORONADO
P A I N T

SECTION NO. 1
ADS -208
88 LINE
Rev. 02/11

Super Kote™ 1000
Vinyl Latex Flat
88 Line



Type	Sheen	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Latex	Flat	300 to 400 Sq. Ft. Per Gallon*	Brush, Roller, Pad or Airless Spray	Clean Water	Clean Soapy Water
Dry Time:		Tack Free: 30 Minutes	Recoat: 4 Hours	Full Cure: 10 Days	

PRODUCT NAME: Super Kote 1000™ Vinyl Latex Flat	This Latex Flat Coating is designed to provide good dry hide and an excellent flat finish when applied to properly prepared surfaces. It is easy to apply and exhibits good touch-up properties.	
WHERE TO USE:	Drywall Plaster Wood Cement Block Metal	Primarily designed as a coating for interior wall surfaces where a flat finish is desired. Ideal for rental property. NOTE: Not for use in high abuse areas that are frequently washed or scrubbed.

REGULATORY INFORMATION:	VOC/VOS STATEMENT:	OTC CATEGORY:	MPI / LEED:
	The products supported by this data sheet contain a maximum of 30 grams per liter VOC / VOS (0.25 lbs/gal.) excluding water & exempt solvents.	This product is compliant under the Ozone Transport Commission regulations as a Flat Coating.	This product is not currently certified under MPI. This product does meet qualifications for LEED (Leadership in Energy and Environmental Design) projects as a flat coating.

SURFACE PREPARATION:	<p>New Work: The surface to be coated must be clean and free of dust, grease, wax, rust, oil and bleeding stains.</p> <p>PRIMING:</p> <p>Drywall – Self priming, but for best results use 40-11 or 948-11 Latex Primer Sealer Plaster – Self Priming, but for best results use 40-11 or 948-11 Latex Primer Sealer Block – Use CORONADO® Block Filler 958-11 Wood – Alkyd Primer Undercoat 37-11 or Latex Enamel Undercoat 78-11 Ferrous Metal – Rust Inhibiting Metal Primer such as 35-11, 35-147, 35-153 or 36-11 Non-Ferrous Metal – Use Grip & Seal™ 116-11 Galvanized – Use Grip & Seal™ 116-11 Smooth Masonry – Masonry Sealer 48-11</p> <p>Repaint Work: On previously painted surfaces in good repair, no priming is generally necessary. On glossy surfaces remove the sheen with sandpaper or steel wool. Patch holes or cracks with appropriate filler. Spot prime bare areas with indicated primer. Remove any oil, chalk, dirt, wax or dust prior to recoating. Any loose or flaking paint should be removed and the edges feather sanded to produce a smooth, uniform surface.</p>
-----------------------------	---

APPLICATION:	<p>Stir product thoroughly with a circular, lifting motion to ensure uniformity throughout before beginning to paint.</p> <p>Roller – 3/8" to 1 1/4" nap, depending on surface texture Brush – Nylon or polyester filament Airless Spray – Tip size and atomization pressures will vary with type of equipment, viscosity and temperature. A tip size of .017 to .021 will provide the most satisfactory spray pattern.</p> <p>Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains. Apply when surface temperature is above 50° F.</p>
* NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
RESIN TYPE:	Vinyl Acetate Acrylic
SOLIDS:	Weight: 38.5 ± 1.0% Volume: 22.5 ± 1.0%
WEIGHT PER GALLON:	10.5 lbs.
VISCOSITY:	110 - 115 KU (Krebs Units)
FLASH POINT:	200° F. or greater (TT-P-141, Method 4293)
SPECULAR GLOSS:	0 – 3 units @ 85 Degrees
SAG RATING:	Pass 8 mils (Leneta)
REC. FILM THICKNESS:	Wet: 4.0 to 5.3 mils Dry: 0.9 to 1.2 mils
LIGHT REFLECTANCE:	89% (White or lightest colors)
CAUTIONS:	<p style="text-align: center;">CAUTION!</p> <p style="text-align: center;">Use only with adequate ventilation.</p> <p>Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.</p> <p style="text-align: center;">Contains Crystalline Silica</p> <p>First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p>WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p>