
INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.399

ACGIH TLV/TWA: 50 ppm - TWA (Skin)
ACGIH TLV/STEL: 150 ppm - STEL (Skin)
OSHA PEL/TWA: 200 ppm - TWA
OSHA STEL: 150 ppm
OSHA CEILING: 300 ppm
LD50: Oral (Rat) - 636 mg/kg
CA PROPOSITION 65: Yes

5

CAS# 67-63-0
ISOPROPYL ALCOHOL
PCT BY WT: 15 - 20 VAPOR PRESSURE: 33.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 400 ppm - TWA
ACGIH TLV/STEL: 500 ppm - STEL
OSHA PEL/TWA: 400 ppm - TWA
OSHA STEL: 500 ppm
LC50: Rat (8 Hrs) - > 12,000 ppm
LD50: Oral (Rat) - 5840 mg/kg

6 n-BUTYL ACETATE

CAS# 123-86-4
ACETIC ACID BUTYL ESTER
PCT BY WT: 15 - 20 VAPOR PRESSURE: 10.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 150 ppm (Proposed)
ACGIH TLV/STEL: STEL 200 ppm
OSHA PEL/TWA: TWA 150 ppm
OSHA STEL: 200 ppm
LC50: Inhalation (Rat) - > 1800 ppm/6 Hrs
LD50: Oral (Rat)- 14,130 mg/kg

7 ACETONE

CAS# 67-64-1
2-PROPANONE
PCT BY WT: 10 - 15
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 500 ppm
ACGIH TLV/STEL: STEL 750 ppm
OSHA PEL/TWA: TWA 750 ppm
OSHA STEL: 1000 ppm
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
LD50: Oral (Rat): 6715 - 8453 mg/kg
CA PROPOSITION 65: No

8

CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: 2.3990 VAPOR PRESSURE: 7.000 MMHG @ 68F
EXPOSURE LIMIT:

ACGIH TLV/TWA:

TWA 100 ppm

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.399

ACGIH TLV/STEL: STEL 25 ppm
OSHA PEL/TWA: TWA 100 ppm
OSHA STEL: 125 ppm
LD50: Oral, Rat - 3500 mg/kg
CA PROPOSITION 65: Yes

9 TALC
MAGNESIUM SILICATE HYDRATE
PCT BY WT: .5 - 5
EXPOSURE LIMIT:

ACGIH TLV/TWA: 2 mg/cu m TWA (Respirable fraction)
OSHA PEL/TWA: 2 mg/cu m TWA (Respirable dust)

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains pigments, which may become a dust nuisance when
removed by abrasive blasting, sanding, or grinding.

This product contains one or more reported or suspected reproductive
toxins.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Causes eye irritation.
SKIN: Prolonged or repeated skin contact may cause drying, cracking
or irritation.
INHALATION: High vapor concentrations may cause drowsiness and
irritation of the eyes or respiratory tract.
INGESTION: Swallowing small amounts of this product during normal
handling is not likely to cause harmful effects, but
swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.399

If applicable, refer to the message(s) below.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

XYLENE: Studies have shown a possible association with exposure to xylene and respiratory tract irritation, liver & kidney damage, nausea, and vomiting in humans. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen (Group 2B).

TOLUENE: Intentional abuse, misuse or other massive exposure to toluene may cause multiple organ (liver, kidney, brain cell) damage and/or death. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness.

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

ACETONE: Extensive human experience and animal data indicate that acetone is of low toxicity. However, ingestion of very large amounts or inhalation of extremely high vapor concentrations can cause irritation, nausea, vomiting, confusion, drowsiness, convulsions, and coma with possible liver and kidney injury. Based on animal data and structure-activity relationships, this product is NOT expected to cause nervous system damage.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.

INGESTION: Seek medical advice.

NOTE TO PHYSICIAN:

Not Applicable.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.399

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH for protection against chemicals in Sections (2 &/or 15).

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State	:	LIQUID	
Vapor Pressure	:	33.00	
Vapor Density	:	4.00	
Boiling Point Range	:	Lower - 133.0	øF
		Higher - 285.0	øF
Specific Gravity	:	.909	
Weight per Volume	:	7.5690	LB/GL
VOC - Total (lbs./gal).	:	5.446	
Evaporation Rate	:	5.700	(n-Butyl Acetate = 1)
Volatile by Weight	:	73.9829	
Volatile by Volume	:	81.2400	

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.399

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Discharge, treatment, or disposal may be subject to national, state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
DOT PACKAGING GROUP : PG II
DOT LABEL : FLAMMABLE LIQUID
DOT SHIPPING NAME : PAINT
DOT PLACARD : FLAMMABLE LIQUID
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.399

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

OCTADECANOIC ACID, ZINC SALT
CAS# 557-05-1 PCT BY WT: 2.1860

XYLENE (MIXED ISOMERS)
CAS# 1330-20-7 PCT BY WT: 9.4770

TOLUENE
CAS# 108-88-3 PCT BY WT: 8.3520

ETHYLBENZENE
CAS# 100-41-4 PCT BY WT: 2.3990

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 11/28/2005
Last Revision Date : 08/12/2005
MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 3 Flammability- 3
Reactivity- 2

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□