
INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.5300

4 n-BUTYL ACETATE
CAS# 123-86-4
ACETIC ACID BUTYL ESTER
PCT BY WT: 15 - 20 VAPOR PRESSURE: 10.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 150 ppm (Proposed)
ACGIH TLV/STEL: STEL 200 ppm
OSHA PEL/TWA: TWA 150 ppm
OSHA STEL: 200 ppm
LC50: Inhalation (Rat) - > 1800 ppm/6 Hrs
LD50: Oral (Rat)- 14,130 mg/kg

5 ACETONE
CAS# 67-64-1
2-PROPANONE
PCT BY WT: 5 - 10
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 500 ppm
ACGIH TLV/STEL: STEL 750 ppm
OSHA PEL/TWA: TWA 750 ppm
OSHA STEL: 1000 ppm
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
LD50: Oral (Rat): 6715 - 8453 mg/kg
CA PROPOSITION 65: No

6
CAS# 64-17-5
ETHYL ALCOHOL
PCT BY WT: 10 - 15 VAPOR PRESSURE: 97.700 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 1000 ppm
OSHA PEL/TWA: TWA 1000 ppm
LD50: Oral (Rat) - 7060 mg/kg

7
CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: 1.3130 VAPOR PRESSURE: 7.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 100 ppm
ACGIH TLV/STEL: STEL 25 ppm
OSHA PEL/TWA: TWA 100 ppm
OSHA STEL: 125 ppm
LD50: Oral, Rat - 3500 mg/kg
CA PROPOSITION 65: Yes

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.5300

This product contains one or more Hazardous Air Pollutants.

This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

This product contains one or more reported or suspected reproductive toxins.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Causes eye irritation.

SKIN: Prolonged or repeated skin contact may cause drying, cracking or irritation.

INHALATION: High vapor concentrations may cause drowsiness and irritation of the eyes or respiratory tract.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

If applicable, refer to the message(s) below.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

XYLENE: Studies have shown a possible association with exposure to this product and respiratory tract irritation, liver & kidney damage in humans, nausea and vomiting. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen, Group 2B.

FORMALDEHYDE: May be released by this product through the skin and respiratory tract. It may produce an allergic response in sensitized individuals, and it is regulated as a carcinogen by OSHA. Gas is listed on NTP list of carcinogens, and it has been determined to be carcinogenic in animals by IARC. Controversial epidemiology studies of exposed workers have indicated little or no additional cancer risk related to exposure.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.5300

Vapors may travel considerable distance to a source of ignition and flash back. Prevent build-up of vapors or gases to explosive concentrations.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills, use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams.

CLEAN-UP

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH for protection against chemicals in Sections (2 &/or 15).

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur,

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.5300

state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
DOT PACKAGING GROUP : PG II
DOT LABEL : FLAMMABLE LIQUID
DOT SHIPPING NAME : PAINT
DOT PLACARD : FLAMMABLE LIQUID
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

XYLENE (MIXED ISOMERS)

CAS# 1330-20-7 PCT BY WT: 5.1850

TOLUENE

CAS# 108-88-3 PCT BY WT: 10.4000

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: 1.3130

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 11/28/2005
Last Revision Date : 10/21/2005
MSDS Prepared for :

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1C.5300

MSDS Last Prepared : NONE

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200 (g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA -Z - 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□