
INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1D.33X

4 ETHYLENE GLYCOL m-BUTYL ETHER
CAS# 111-76-2
2-BUTOXYETHANOL
PCT BY WT: 2.0510 VAPOR PRESSURE: .660 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 20 ppm TWA (Skin)
OSHA PEL/TWA: 50 ppm TWA (Skin)
LC50: Inhalation (Mouse) - 700 ppm/7 Hrs
LD50: Oral (Rat)- 1746 mg/kg
CA PROPOSITION 65: No

5 ACETONE
CAS# 67-64-1
2-PROPANONE
PCT BY WT: 5 - 10
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 500 ppm
ACGIH TLV/STEL: STEL 750 ppm
OSHA PEL/TWA: TWA 750 ppm
OSHA STEL: 1000 ppm
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
LD50: Oral (Rat): 6715 - 8453 mg/kg
CA PROPOSITION 65: No

6 ISOBUTYL ALCOHOL
CAS# 78-83-1
2-METHYL-1-PROPANOL
PCT BY WT: .5 - 5 VAPOR PRESSURE: 10.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 50 ppm - TWA
OSHA PEL/TWA: 100 ppm - TWA
LC50: Inhalation (Rat)- >8000 ppm/4 Hour (s)
LD50: Oral (Rat): 2.5-6.4 g/kg

7
CAS# 64-17-5
ETHYL ALCOHOL
PCT BY WT: 15 - 20 VAPOR PRESSURE: 97.700 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 1000 ppm
OSHA PEL/TWA: TWA 1000 ppm
LD50: Oral (Rat) - 7060 mg/kg

8 ISOBUTYL ACETATE
CAS# 110-19-0
2-METHYLPROPYL ACETATE
PCT BY WT: 20 - 25 VAPOR PRESSURE: 18.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 150 ppm
OSHA PEL/TWA: TWA 150 ppm
LC50: Inhalation (Rat, 4Hr.): 3500-3800 ppm

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1D.33X

LD50: Oral (Rat) - > 4350 mg/kg

9

CAS# 141-78-6

ETHYL ACETATE

PCT BY WT: 5 - 10 VAPOR PRESSURE: 76.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: 400 ppm - TWA

OSHA PEL/TWA: 400 ppm - TWA

LC50: Inhalation (Rat) - 1600 ppm/8H

LD50: Oral (Rat) - 5620 mg/kg

10

CAS# 100-41-4

ETHYLBENZENE

PCT BY WT: .3370 VAPOR PRESSURE: 7.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: TWA 100 ppm

ACGIH TLV/STEL: STEL 25 ppm

OSHA PEL/TWA: TWA 100 ppm

OSHA STEL: 125 ppm

LD50: Oral, Rat - 3500 mg/kg

CA PROPOSITION 65: Yes

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains pigments, which may become a dust nuisance when
removed by abrasive blasting, sanding, or grinding.

This product contains one or more reported or suspected reproductive
toxins.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Causes eye irritation.

SKIN: Prolonged or repeated skin contact may cause drying, cracking
or irritation.

INHALATION: High vapor concentrations may cause drowsiness and
irritation of the eyes or respiratory tract.

INGESTION: Swallowing small amounts of this product during normal

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1D.33X

handling is not likely to cause harmful effects, but
swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

If applicable, refer to the message(s) below.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

XYLENE: Studies have shown a possible association with exposure to xylene and respiratory tract irritation, liver & kidney damage, nausea, and vomiting in humans. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen (Group 2B).

TOLUENE: Intentional abuse, misuse or other massive exposure to toluene may cause multiple organ (liver, kidney, brain cell) damage and/or death. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness. Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

ACETONE: Extensive human experience and animal data indicate that acetone is of low toxicity. However, ingestion of very large amounts or inhalation of extremely high vapor concentrations can cause irritation, nausea, vomiting, confusion, drowsiness, convulsions, and coma with possible liver and kidney injury. Based on animal data and structure-activity relationships, this product is NOT expected to cause nervous system damage.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1D.33X

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor respirator approved by NIOSH for protection against chemicals in Section 2 &/or 15.

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State : LIQUID
Vapor Pressure : 97.70
Vapor Density : 4.10
Boiling Point Range : Lower - 133.0 øF
Higher - 343.0 øF
Specific Gravity : .921
Weight per Volume : 7.6676 LB/GL
VOC - Total (lbs./gal). : 5.462
Evaporation Rate : 6.200 (n-Butyl Acetate = 1)
Volatile by Weight : 72.2577
Volatile by Volume : 79.2653

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1D.33X

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Discharge, treatment, or disposal may be subject to national, state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
DOT PACKAGING GROUP : PG II
DOT LABEL : FLAMMABLE LIQUID
DOT SHIPPING NAME : PAINT
DOT PLACARD : FLAMMABLE LIQUID
UN/NA NUMBER : UN1263

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1D.33X

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

XYLENE (MIXED ISOMERS)

CAS# 1330-20-7 PCT BY WT: 1.3300

TOLUENE

CAS# 108-88-3 PCT BY WT: 10.7830

2-BUTOXYETHANOL

CAS# 111-76-2 PCT BY WT: 2.0510

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: .3370

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 11/28/2005
Last Revision Date : 02/11/2005
MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 3 Flammability- 3
Reactivity- 2

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1D.33X

composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□