



-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

1M.430X

-----  
4 5-METHYL-2-HEXANONE  
CAS# 110-12-3  
METHYL ISOAMYL KETONE  
PCT BY WT: .5 - 5 VAPOR PRESSURE: 4.500 MMHG @ 68F  
EXPOSURE LIMIT:  
ACGIH TLV/TWA: 50 ppm TWA  
OSHA PEL/TWA: 100 ppm TWA  
LC50: Inhalation (Rat)- 3813 ppm/6 Hrs  
LD50: Oral (Rat) - 5700 mg/kg

-----  
5  
CAS# 108-65-6  
PROPYLENE GLYCOL m-METHYL ETHER ACETATE  
PCT BY WT: .5 - 5 VAPOR PRESSURE: 3.700 MMHG @ 68F  
EXPOSURE LIMIT:  
LC50: Inhalation (Rat, Male) - > 4345 ppm/6 Hrs  
LD50: Oral (Rat, Female)- 8.5 g/kg

-----  
6 n-BUTYL ACETATE  
CAS# 123-86-4  
ACETIC ACID BUTYL ESTER  
PCT BY WT: 10 - 15 VAPOR PRESSURE: 10.000 MMHG @ 68F  
EXPOSURE LIMIT:  
ACGIH TLV/TWA: TWA 150 ppm (Proposed)  
ACGIH TLV/STEL: STEL 200 ppm  
OSHA PEL/TWA: TWA 150 ppm  
OSHA STEL: 200 ppm  
LC50: Inhalation (Rat) - > 1800 ppm/6 Hrs  
LD50: Oral (Rat)- 14,130 mg/kg

-----  
7 ACETONE  
CAS# 67-64-1  
2-PROPANONE  
PCT BY WT: 5 - 10  
EXPOSURE LIMIT:  
ACGIH TLV/TWA: TWA 500 ppm  
ACGIH TLV/STEL: STEL 750 ppm  
OSHA PEL/TWA: TWA 750 ppm  
OSHA STEL: 1000 ppm  
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs  
LD50: Oral (Rat): 6715 - 8453 mg/kg  
CA PROPOSITION 65: No

-----  
8 ISOBUTYL ALCOHOL  
CAS# 78-83-1  
2-METHYL-1-PROPANOL  
PCT BY WT: 5 - 10 VAPOR PRESSURE: 10.000 MMHG @ 68F  
EXPOSURE LIMIT:  
ACGIH TLV/TWA: 50 ppm - TWA  
OSHA PEL/TWA: 100 ppm - TWA  
LC50: Inhalation (Rat)- >8000 ppm/4 Hour (s)

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

1M.430X

-----  
LD50: Oral (Rat): 2.5-6.4 g/kg  
-----

9

CAS# 100-41-4  
ETHYLBENZENE

PCT BY WT: 2.5550 VAPOR PRESSURE: 7.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: TWA 100 ppm  
ACGIH TLV/STEL: STEL 25 ppm  
OSHA PEL/TWA: TWA 100 ppm  
OSHA STEL: 125 ppm  
LD50: Oral, Rat - 3500 mg/kg  
CA PROPOSITION 65: Yes

-----  
10

CAS# 112926-00-8  
SYNTHETIC AMORPHOUS SILICA

PCT BY WT: .5 - 5

EXPOSURE LIMIT:

ACGIH TLV/TWA: 10 mg/cu m  
OSHA PEL/TWA: 6 mg/cu m  
LC50: Rat - > 2 mg/L (1 Hr)  
LD50: Oral (Rat) - > 31,600 mg/kg

-----  
\*\*\*\*\*  
This product contains one or more reported carcinogens or suspected  
carcinogens which are noted in Section 3, Hazards Identification,  
CARCINOGENICITY.  
\*\*\*\*\*

\*\*\*\*\*  
This product contains one or more Hazardous Air Pollutants.  
\*\*\*\*\*

\*\*\*\*\*  
This product contains pigments, which may become a dust nuisance when  
removed by abrasive blasting, sanding, or grinding.  
\*\*\*\*\*

\*\*\*\*\*  
This product contains one or more reported or suspected reproductive  
toxins.  
\*\*\*\*\*

-----  
SECTION 3 - HAZARDS IDENTIFICATION  
-----

POTENTIAL HEALTH EFFECTS

EYES: Causes eye irritation.  
SKIN: Prolonged or repeated skin contact may cause drying, cracking  
or irritation.  
INHALATION: High vapor concentrations may cause drowsiness and  
irritation of the eyes or respiratory tract.  
INGESTION: Swallowing small amounts of this product during normal

---

INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

1M.430X

---

handling is not likely to cause harmful effects, but  
swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

If applicable, refer to the message(s) below.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

**XYLENE:** Studies have shown a possible association with exposure to xylene and respiratory tract irritation, liver & kidney damage, nausea, and vomiting in humans. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen (Group 2B).

**TOLUENE:** Intentional abuse, misuse or other massive exposure to toluene may cause multiple organ (liver, kidney, brain cell) damage and/or death. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness. Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

**ACETONE:** Extensive human experience and animal data indicate that acetone is of low toxicity. However, ingestion of very large amounts or inhalation of extremely high vapor concentrations can cause irritation, nausea, vomiting, confusion, drowsiness, convulsions, and coma with possible liver and kidney injury. Based on animal data and structure-activity relationships, this product is NOT expected to cause nervous system damage.

---

SECTION 4 - FIRST AID MEASURES

---

EMERGENCY FIRST AID:

**EYE CONTACT:** Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

**SKIN CONTACT:** Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.



-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET  
-----

1M.430X  
-----

SECTION 7 - HANDLING AND STORAGE  
-----

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.  
-----

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION  
-----

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor respirator approved by NIOSH for protection against chemicals in Section 2 &/or 15.

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.  
-----

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Physical State . . . . .	: LIQUID		
Vapor Pressure . . . . .	: 33.00		
Vapor Density . . . . .	: 4.60		
Boiling Point Range . . . . .	: Lower - 133.0	øF	
	: Higher - 302.0	øF	
Specific Gravity . . . . .	: .952		
Weight per Volume . . . . .	: 7.9219	LB/GL	
VOC - Total (lbs./gal). . . . .	: 4.808		
Evaporation Rate . . . . .	: 5.700	(n-Butyl Acetate = 1)	
Volatile by Weight . . . . .	: 62.1102		
Volatile by Volume . . . . .	: 69.6138		

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET  
-----

1M.430X  
-----

-----  
SECTION 10 - STABILITY AND REACTIVITY  
-----

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.  
-----

SECTION 11 - TOXICOLOGICAL INFORMATION  
-----

No data at this time.  
-----

SECTION 12 - ECOLOGICAL INFORMATION  
-----

No data at this time.  
-----

SECTION 13 - DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL

Discharge, treatment, or disposal may be subject to national, state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.  
-----

SECTION 14 - TRANSPORT INFORMATION  
-----

DOT HAZARD CLASS . . . . . : 3  
DOT PACKAGING GROUP . . . . . : PG II  
DOT LABEL . . . . . : FLAMMABLE LIQUID  
DOT SHIPPING NAME . . . . . : PAINT  
DOT PLACARD . . . . . : FLAMMABLE LIQUID  
UN/NA NUMBER . . . . . : UN1263

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

1M.430X  
-----

-----  
SECTION 15 - REGULATORY INFORMATION  
-----

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

XYLENE (MIXED ISOMERS)

CAS# 1330-20-7 PCT BY WT: 10.0910  
-----

TOLUENE

CAS# 108-88-3 PCT BY WT: 9.7920  
-----

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: 2.5550  
-----

-----  
SECTION 16 - OTHER INFORMATION  
-----

Prepared by . . . . . :  
Date of issue . . . . . : 11/21/2005  
Last Revision Date . . . . . : 06/17/2005  
MSDS Prepared for . . . . . :  
MSDS Last Prepared . . . . . : NONE  
HMIS Rating: Health- 3 Flammability- 3  
Reactivity- 2

\*\*\*\*\*

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET  
-----

1M.430X

\*\*\*\*\*  
Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m<sup>3</sup> or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□