
INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1M.80X

4

CAS# 108-65-6
PROPYLENE GLYCOL m-METHYL ETHER ACETATE
PCT BY WT: .5 - 5 VAPOR PRESSURE: 3.700 MMHG @ 68F
EXPOSURE LIMIT:
LC50: Inhalation (Rat, Male) - > 4345 ppm/6 Hrs
LD50: Oral (Rat, Female)- 8.5 g/kg

5 n-BUTYL ACETATE

CAS# 123-86-4
ACETIC ACID BUTYL ESTER
PCT BY WT: .5 - 5 VAPOR PRESSURE: 10.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 150 ppm (Proposed)
ACGIH TLV/STEL: STEL 200 ppm
OSHA PEL/TWA: TWA 150 ppm
OSHA STEL: 200 ppm
LC50: Inhalation (Rat) - > 1800 ppm/6 Hrs
LD50: Oral (Rat)- 14,130 mg/kg

6 ETHYLENE GLYCOL m-BUTYL ETHER

CAS# 111-76-2
2-BUTOXYETHANOL
PCT BY WT: 1.5850 VAPOR PRESSURE: .660 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 20 ppm TWA (Skin)
OSHA PEL/TWA: 50 ppm TWA (Skin)
LC50: Inhalation (Mouse) - 700 ppm/7 Hrs
LD50: Oral (Rat)- 1746 mg/kg
CA PROPOSITION 65: No

7 ACETONE

CAS# 67-64-1
2-PROPANONE
PCT BY WT: 5 - 10
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 500 ppm
ACGIH TLV/STEL: STEL 750 ppm
OSHA PEL/TWA: TWA 750 ppm
OSHA STEL: 1000 ppm
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
LD50: Oral (Rat): 6715 - 8453 mg/kg
CA PROPOSITION 65: No

8 ISOBUTYL ALCOHOL

CAS# 78-83-1
2-METHYL-1-PROPANOL
PCT BY WT: 10 - 15 VAPOR PRESSURE: 10.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 50 ppm - TWA
OSHA PEL/TWA: 100 ppm - TWA

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1M.80X

LC50: Inhalation (Rat)- >8000 ppm/4 Hour (s)
LD50: Oral (Rat): 2.5-6.4 g/kg

9

CAS# 64-17-5
ETHYL ALCOHOL
PCT BY WT: .5 - 5 VAPOR PRESSURE: 97.700 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 1000 ppm
OSHA PEL/TWA: TWA 1000 ppm
LD50: Oral (Rat) - 7060 mg/kg

10 ISOBUTYL ACETATE

CAS# 110-19-0
2-METHYLPROPYL ACETATE
PCT BY WT: 15 - 20 VAPOR PRESSURE: 18.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 150 ppm
OSHA PEL/TWA: TWA 150 ppm
LC50: Inhalation (Rat, 4Hr.): 3500-3800 ppm
LD50: Oral (Rat)- > 4350 mg/kg

11

CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: 1.0820 VAPOR PRESSURE: 7.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 100 ppm
ACGIH TLV/STEL: STEL 25 ppm
OSHA PEL/TWA: TWA 100 ppm
OSHA STEL: 125 ppm
LD50: Oral, Rat - 3500 mg/kg
CA PROPOSITION 65: Yes

12

CAS# 13463-67-7
TITANIUM DIOXIDE
PCT BY WT: 20 - 25
EXPOSURE LIMIT:
ACGIH TLV/TWA: 10 mg/cu m(Total Dust) - TWA
OSHA PEL/TWA: 10 mg/cu m(Total Dust) - TWA
LD50: Oral (Rat)- >7500 mg/kg (TiO2)

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1M.80X

This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

This product contains one or more reported or suspected reproductive toxins.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Causes eye irritation.

SKIN: Prolonged or repeated skin contact may cause drying, cracking or irritation.

INHALATION: High vapor concentrations may cause drowsiness and irritation of the eyes or respiratory tract.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

If applicable, refer to the message(s) below.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

XYLENE: Studies have shown a possible association with exposure to xylene and respiratory tract irritation, liver & kidney damage, nausea, and vomiting in humans. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen (Group 2B).

TOLUENE: Intentional abuse, misuse or other massive exposure to toluene may cause multiple organ (liver, kidney, brain cell) damage and/or death. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness.

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1M.80X

Vapors may travel considerable distance to a source of ignition and flash back. Prevent build-up of vapors or gases to explosive concentrations.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills, use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams.

CLEAN-UP

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor respirator approved by NIOSH for protection against chemicals in Section 2 &/or 15.

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur,

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1M.80X

state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
DOT PACKAGING GROUP : PG II
DOT LABEL : FLAMMABLE LIQUID
DOT SHIPPING NAME : PAINT
DOT PLACARD : FLAMMABLE LIQUID
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

XYLENE (MIXED ISOMERS)

CAS# 1330-20-7 PCT BY WT: 4.2760

TOLUENE

CAS# 108-88-3 PCT BY WT: 4.6940

2-BUTOXYETHANOL

CAS# 111-76-2 PCT BY WT: 1.5850

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: 1.0820

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 11/28/2005
Last Revision Date : 02/18/2005

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1M.80X

MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 3 Flammability- 3
 Reactivity- 2

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□