
INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1Y.935

INHALATION: Causes mild respiratory irritation. Breathing large amounts may be harmful. Symptoms of exposure may include irritation (nose, throat, respiratory tract) and CNS depression.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

CHRONIC EFFECTS

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause respiratory and/or skin sensitization.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT

If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water, holding eyelids apart. If symptoms persist, seek medical attention.

SKIN CONTACT

Remove contaminated shoes and clothing, and flush affected area with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area thoroughly by washing with mild soap and water. If irritation or redness develops, seek medical attention. Launder clothing before reuse.

INHALATION

If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention. Keep person warm & quiet.

INGESTION

Aspiration hazard. Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If the victim is drowsy or unconscious, place on left side with head down. If possible, do not leave victim unattended. Seek immediate medical attention.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1Y.935

NOTE TO PHYSICIAN:
Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : Combustible Liquid-Class II
Flashpoint : > 100 Deg. F, but < 140 Deg. F.
Explosion Level : Low - .9
High - 7.0

EXTINGUISHING MEDIA

Use National Fire Protection Association (NFPA) Class B extinguisher (carbon dioxide, dry chemical or foam).

FIRE-FIGHTING INSTRUCTIONS

During fire, a water spray can scatter flames and should be used by experienced firefighters. Firefighters should wear self-contained breathing apparatus with a full face piece operated in the positive pressure mode when fighting fires. Isolate damage area, keep unauthorized personnel out. Avoid spreading burning liquid with water used for cooling purposes.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Combustible liquid. Forms combustible mixtures with air at or above the flash point. This product can accumulate static charges, which can cause fire or explosion. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode and flash back.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all ignition sources. Spilled material may be absorbed into an appropriate absorbent material. Prevent spilled material from entering sewers, storm drains, other authorized treatment drainage systems, and natural waterways. Stop spill/release if it can be done, and stay away from spill. Isolate danger and keep unauthorized personnel out. Use non-sparking tools and explosion-proof equipment.

CLEAN-UP

Warn occupants in surrounding and downwind areas of fire and explosion hazard to stay clear. Remove from surface with suitable absorbents. If allowed by local authorities, sinking and/or suitable dispersants may be used in non-confined waters.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1Y.935

Weight per Volume : 7.3480 LB/GL
VOC - Total (lbs./gal). : 3.682
Evaporation Rate : .300 (n-Butyl Acetate = 1)
Volatile by Weight : 50.1110
Volatile by Volume : 57.9811

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents such as chlorine, oxygen, or strong oxidizing acids, such as, nitric and sulfuric.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

Avoid heat, sparks, open flames and other sources of ignition.

HAZARDOUS PRODUCTS OF DECOMPOSITION

Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : NOT REGULATED (In containers less than 119 gallons or 450 liters via surface transportation).

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1Y.935

COMBUSTIBLE LIQUID (In containers of more than 119 gallons capacity)
for surface shipments within the U.S. and Canada, and apply the DOT
information, listed below:

DOT PACKAGING GROUP : PG III
DOT LABEL : NONE
DOT SHIPPING NAME : PAINT
DOT PLACARD : NONE
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic
Substances Control Act (TSCA) inventory of chemicals or are otherwise
compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the
reporting requirements of Section 313 of Title III of the Superfund
Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

1,2,4-TRIMETHYLBENZENE

CAS# 95-63-6 PCT BY WT: 1.3380

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 12/15/2005
Last Revision Date : 03/31/2005
MSDS Prepared for :
MSDS Last Prepared : NONE

HMIS Rating: Health- 2 Flammability- 2
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication
Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1Y.935

and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□