
COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M3000.1.1

PCT BY WT: 1 - 5
EXPOSURE LIMIT:
ACGIH TLV/TWA: Fume: TWA 5 mg/cu m
ACGIH TLV/STEL: STEL 10 mg/cu m
OSHA PEL/TWA: Fume: TWA 5 mg/cu m; TWA Total Dust: 10 mg/cu m
OSHA STEL: Fume: 10 mg/cu m
LC50: Inhalation, Mouse - 2500 mg/cu m
LD50: Oral, Mouse - 7950 mg/kg

This product contains one or more Hazardous Air Pollutants.

This product contains no reported carcinogens or suspected carcinogens according to the information provided in Section 3 of this MSDS.

This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

This product contains one or more reported or suspected reproductive toxins.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS
EYES: Primary irritant.
SKIN: N/A
INHALATION: With poor ventilation, vapor or spray mist may irritate respiratory mucous membranes, causing headache & nausea.
INGESTION: N/A
CHRONIC EFFECTS:
Ethylene glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans. Prolonged overexposure to ethylene glycol may cause adverse effects to the reproductive system.
ROUTE(S) OF EXPOSURE
Exposure may be inhalation and/or skin or eye contact, depending on conditions of use.
CARCINOGENICITY
No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M3000.1.1

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.

INGESTION: If victim is conscious, give 2 glasses of water to dilute. Do not induce vomiting. Consult physician or poison control center at once.

NOTE TO PHYSICIAN:

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : N/A

Flashpoint : N/A

Explosion Level : Low - .9
High - 15.3

EXTINGUISHING MEDIA

Use extinguishing media appropriate for surrounding fire. After water evaporates, remaining material will burn; use CO2, dry chemical or foam (National Fire Protection Association Class B extinguisher).

FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat; use water spray to cool. Product in open containers may spatter when the temperature exceeds boiling point of water.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Ventilate as described in Section 8. Avoid unnecessary skin contact. Stop and/or contain spill if it can be done safely. Avoid discharge into drains, sewers or waterways.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M3000.1.1

Volatile by Weight : 49.7548
Volatile by Volume : 64.9722

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

None known.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS PRODUCTS OF DECOMPOSITION

Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : N/A
DOT PACKAGING GROUP : N/A
DOT LABEL : NONE
DOT SHIPPING NAME : PAINT
DOT PLACARD : NONE
UN/NA NUMBER : NONE

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M3000.1.1

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLENE GLYCOL

CAS# 107-21-1 PCT BY WT: 2.7500

ZINC OXIDE

CAS# 1314-13-2 PCT BY WT: 1 - 5

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 09/09/2009
Last Revision Date : 09/02/2009
MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 1 Flammability- 0
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M3000.1.1

Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.