

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID : TLB395
PRODUCT CLASS : CELLULOSE LACQUER, SOLVENT BASED
TRADE NAME : LACQUER UNDERCOATER - WHITE
MSDS PREPARATION DATE : 06/20/2007

MANUFACTURER IDENTIFICATION:

NAME : INSL-X PRODUCTS CORPORATION
ADDRESS : 50 HOLT DRIVE
STONY POINT, NY 10980
TELEPHONE : (800) 225-5554
EMERGENCY CONTACT : CHEMTREC
EMERGENCY TELEPHONE : (800) 424-9300

SECTION 2 - COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

1 VM & P NAPHTHA

CAS# 64742-89-8

ALIPHATIC PETROLEUM DISTILLATES

PCT BY WT: 5 - 10 VAPOR PRESSURE: 10.200 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: 300 ppm TWA
OSHA PEL/TWA: 300 ppm TWA
OSHA STEL: 400 ppm
LC50: Inhalation (Rat) - 3400 ppm/4H
LD50: Oral (Rat) - > 8 ml/kg
CA PROPOSITION 65: No

2

CAS# 108-88-3

TOLUENE

PCT BY WT: 19.2020 VAPOR PRESSURE: 22.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: 50 ppm - TWA (Skin)
ACGIH TLV/STEL: 150 ppm - STEL (Skin)
OSHA PEL/TWA: 200 ppm - TWA
OSHA STEL: 150 ppm
OSHA CEILING: 300 ppm
LD50: Oral (Rat) - 636 mg/kg
CA PROPOSITION 65: Yes

3

CAS# 67-63-0

ISOPROPYL ALCOHOL

PCT BY WT: 5 - 10 VAPOR PRESSURE: 33.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: 200 ppm - TWA
ACGIH TLV/STEL: 400 ppm - STEL
OSHA PEL/TWA: 400 ppm - TWA
OSHA STEL: 500 ppm
LC50: Rat (8 Hrs) - > 12,000 ppm
LD50: Oral (Rat) - 5000 mg/kg

4 METHANOL

CAS# 67-56-1

METHYL ALCOHOL

PCT BY WT: 3.8500 VAPOR PRESSURE: 98.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: 200 ppm - TWA (Skin)

ACGIH TLV/STEL: 250 ppm - STEL (Skin)
OSHA PEL/TWA: 200 ppm - TWA
OSHA STEL: 250 ppm - STEL(Skin)
LC50: Inhalation (Rat) - 64,000 ppm/4H
LD50: Oral (Rat) - 5628 mg/kg

5 n-BUTYL ACETATE
CAS# 123-86-4
ACETIC ACID BUTYL ESTER
PCT BY WT: 5 - 10 VAPOR PRESSURE: 15.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 150 ppm
ACGIH TLV/STEL: STEL 200 ppm
OSHA PEL/TWA: TWA 150 ppm
OSHA STEL: 200 ppm
LC50: Inhalation (Rat) - > 1800 ppm/6 Hrs
LD50: Oral (Rat)- 14,130 mg/kg

6 ACETONE
CAS# 67-64-1
2-PROPANONE
PCT BY WT: .5 - 5 VAPOR PRESSURE: 185.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 500 ppm
ACGIH TLV/STEL: STEL 750 ppm
OSHA PEL/TWA: TWA 750 ppm
OSHA STEL: 1000 ppm
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
LD50: Oral (Rat): 6715 - 8453 mg/kg
CA PROPOSITION 65: No

7
CAS# 141-78-6
ETHYL ACETATE
PCT BY WT: 5 - 10 VAPOR PRESSURE: 93.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: 400 ppm - TWA
OSHA PEL/TWA: 400 ppm - TWA
LC50: Inhalation (Rat) - 1600 ppm/8H
LD50: Oral (Rat) - >5620 mg/kg

8
CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: .2030 VAPOR PRESSURE: 7.000 MMHG @ 68F
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 100 ppm
ACGIH TLV/STEL: STEL 25 ppm
OSHA PEL/TWA: TWA 100 ppm
OSHA STEL: 125 ppm
LD50: Oral, Rat - 3500 mg/kg
CA PROPOSITION 65: Yes

9
CAS# 14808-60-7
CRYSTALLINE SILICA - QUARTZ
PCT BY WT: .2570
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 0.10 mg/cu m (Respirable Dust)
OSHA PEL/TWA: TWA 0.10 mg/cu m (Respirable Fraction)
CA PROPOSITION 65: Yes

This product contains one or more reported carcinogens or suspected carcinogens which are noted in Section 3, Hazards Identification, CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

This product contains one or more reported or suspected reproductive toxins.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

- EYES: Causes eye irritation.
- SKIN: Prolonged or repeated skin contact may cause drying, cracking or irritation.
- INHALATION: High vapor concentrations may cause drowsiness and irritation of the eyes or respiratory tract.
- INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen, Group 2B.

IARC and NTP have reviewed crystalline silica. IARC found sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources. Long-term overexposure to crystalline silica causes silicosis, a form of pulmonary fibrosis. Continued overexposure to silica can lead to cardiopulmonary impairment.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

- TOLUENE: Intentional abuse, misuse or other massive exposure to toluene may cause multiple organ (liver, kidney, brain cell) damage and/or death. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness. Toluene may be harmful to the human fetus based on positive test results with laboratory animals.
- ACETONE: Extensive human experience and animal data indicate that acetone is of low toxicity. However, ingestion of very large amounts or inhalation of extremely high vapor concentrations can cause irritation, nausea, vomiting, confusion, drowsiness, drowsiness, convulsions, and coma with possible liver and kidney injury. Based on animal data and structure-activity relationships, this product is NOT expected to cause nervous system damage.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.

INGESTION: Seek medical advice.

NOTE TO PHYSICIAN:

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : OSHA Flammable Liquid - Class 1B
Flashpoint : 10.0 øF
Explosion Level : Low - .9
High - 36.0

EXTINGUISHING MEDIA

Water spray, dry chemical, carbon dioxide (CO2), alcohol foam

SPECIAL FIRE-FIGHTING PROCEDURES

Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. The fire could easily be spread by the use of water in an area where the water could not be contained. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS

FLAMMABLE. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent build-up of vapors or gases to explosive concentrations.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills, use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams.

CLEAN-UP

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin.

Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH for protection against chemicals in Sections (2 &/or 15).

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State	:	LIQUID	
Vapor Pressure	:	185.00	
Vapor Density	:	10.80	
Boiling Point Range	:	Lower - 133.0	øF
		Higher - 285.0	øF
Specific Gravity	:	1.124	
Weight per Volume	:	9.3590	LB/GL
VOC - Total (lb/gal).	:	5.369	
Evaporation Rate	:	14.400	(n-Butyl Acetate = 1)
Volatile by Weight	:	57.9431	
Volatile by Volume	:	78.1719	

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Discharge, treatment, or disposal may be subject to national, state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode

on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
DOT PACKAGING GROUP : PG II
DOT LABEL : FLAMMABLE LIQUID
DOT SHIPPING NAME : PAINT
DOT PLACARD : FLAMMABLE LIQUID
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOLUENE

CAS# 108-88-3 PCT BY WT: 19.2020

METHYL ALCOHOL

CAS# 67-56-1 PCT BY WT: 3.8500

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: .2030

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 06/20/2007
Last Revision Date : 12/29/2006
MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 2 Flammability- 3
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC -

Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.