

LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
 LD50: Oral (Rat): 6715 - 8453 mg/kg
 CA PROPOSITION 65: No

6 DIISOBUTYL KETONE
 CAS# 108-83-8
 2,6-DIMETHYL-4-HEPTANONE

PCT BY WT: .5 - 5 VAPOR PRESSURE: 1.700 MMHG @ 68F
 EXPOSURE LIMIT:
 ACGIH TLV/TWA: TLV 25 ppm - TWA
 OSHA PEL/TWA: PEL 50 ppm - TWA
 LD50: Oral,Rat - 5750 mg/kg

7 2-HEPTANONE
 CAS# 110-43-0
 METHYL n-AMYL KETONE

PCT BY WT: .5 - 5 VAPOR PRESSURE: 2.140 MMHG @ 68F
 EXPOSURE LIMIT:
 ACGIH TLV/TWA: 50 ppm - TWA
 OSHA PEL/TWA: 100 ppm - TWA
 LC50: Inhalation,Rat: 2000- 4000 ppm/4 Hrs
 LD50: Oral, Rats - 1600 mg/kg

8
 CAS# MIXTURE
 NITROCELLULOSE CHIP

PCT BY WT: .5 - 5
 EXPOSURE LIMIT:
 LD50: >2000 mg/kg ORAL RAT

 This product contains no reported carcinogens or suspected carcinogens according to the information provided in Section 3 of this MSDS.

 This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Causes eye irritation.
 SKIN: Prolonged or repeated skin contact may cause drying, cracking or irritation.
 INHALATION: High vapor concentrations may cause drowsiness and irritation of the eyes or respiratory tract.
 INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

ACETONE: Extensive human experience and animal data indicate that acetone is of low toxicity. However, ingestion of very large amounts or inhalation of extremely high vapor concentrations can cause irritation, nausea, vomiting, confusion, drowsiness, drowsiness, convulsions, and coma with possible liver and kidney injury. Based on animal data and structure-activity relationships, this product is NOT expected to cause nervous system damage.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.

INGESTION: Seek medical advice.

NOTE TO PHYSICIAN:

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

| | |
|---------------------------------------|------------------------------------|
| Flammability Classification | : OSHA Flammable Liquid - Class 1B |
| Flashpoint | : 1.0 øF |
| Explosion Level | : Low - .8 |
| | High - 12.8 |

EXTINGUISHING MEDIA

Water spray, dry chemical, carbon dioxide (CO2), alcohol foam

SPECIAL FIRE-FIGHTING PROCEDURES

Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. The fire could easily be spread by the use of water in an area where the water could not be contained. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Extremely Flammable. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills, use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams.

CLEAN-UP

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH for protection against chemicals in Sections (2 &/or 15).

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------------------|---|----------------|-----------------------|
| Physical State | : | LIQUID | |
| Vapor Pressure | : | 185.00 | |
| Vapor Density | : | 10.80 | |
| Boiling Point Range | : | Lower - 133.0 | øF |
| | | Higher - 343.0 | øF |
| Specific Gravity | : | .882 | |
| Weight per Volume | : | 7.3421 | LB/GL |
| VOC - Total (lb/gal). | : | 2.285 | |
| Evaporation Rate | : | 14.400 | (n-Butyl Acetate = 1) |
| Volatile by Weight | : | 71.5858 | |
| Volatile by Volume | : | 78.8484 | |

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Discharge, treatment, or disposal may be subject to national, state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
 DOT PACKAGING GROUP : PG II
 DOT LABEL : FLAMMABLE LIQUID
 DOT SHIPPING NAME : PAINT
 DOT PLACARD : FLAMMABLE LIQUID
 UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION 16 - OTHER INFORMATION

Prepared by : INSL-X PRODUCTS CORP.
 Date of issue : 08/29/2007
 Last Revision Date : 08/28/2007

MSDS Prepared for :
 MSDS Last Prepared : NONE
 HMIS Rating: Health- 2 Flammability- 3
 Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of

reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.